SIEMENS

Data sheet

6GK5798-1LP00-0AA6

product type designation



LP798-1PRO lightning protector

interfaces	
number of electrical connections	2
type of electrical connection	RSMA Connector
design of plug-in connection	male / female
electrical data	
transmission frequency	0 6000 MHz
impedance	50 Ω
ambient conditions	
ambient temperature	
 during operation 	-40 +85 °C
 during storage 	-40 +85 °C
 during transport 	-40 +85 °C
suitability for use	
 for interior use 	Yes
 for outside use 	Yes
protection class IP	IP65
design, dimensions and weights	
width	35.3 mm
diameter	15 mm
net weight	50 g
product features, product functions, product components	/ general
product feature / silicon-free	Yes
further information / internet-Links	
Internet-Link	
 to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
 to website: Industrial communication 	http://www.siemens.com/simatic-net
 to website: Industry Mall 	https://www.siemens.com/industrymall
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
 to website: Image database 	http://automation.siemens.com/bilddb
 to website: CAx-Download-Manager 	http://www.siemens.com/cax
 to website: Industry Online Support 	https://support.industry.siemens.com
last modified:	1/21/2021 🖸