

product description

XR-300 media module

SCALANCE X accessory; Media module MM992-2LD; 2x 1000 Mbit/s SC-ports, optical; single-mode optical up to max. 10 km.



| interfaces | |
|--|--|
| number of electrical/optical connections / for network components or terminal equipment / maximum | 2 |
| number of optical interfaces / for network components or terminal equipment / maximum | 2 |
| number of 1000 Mbit/s SC ports (LX) | 2 |
| design of the optical interface / for network components or terminal equipment | SC |
| wavelength / of the optical interface | 1310 nm; Single-mode |
| connectable optical power relative to 1 mW <ul style="list-style-type: none"> of the transmitter output / minimum of the transmitter output / maximum of the receiver input / maximum | -9.5 dB -3 dB -3 dB |
| optical sensitivity relating to 1 mW / of the receiver input / minimum | -21 dB |
| attenuation factor / of the FOC transmission link / minimum necessary | 0 dB |
| range / at the optical interface / depending on the optical fiber used | 0 ... 10 km |
| ambient conditions | |
| ambient temperature <ul style="list-style-type: none"> during operation during storage during transport | -40 ... +70 °C -40 ... +85 °C -40 ... +85 °C |
| relative humidity / at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP20 |
| design, dimensions and weights | |
| design | Media module |
| width | 60 mm |
| height | 22 mm |
| depth | 100 mm |
| net weight | 0.08 kg |
| fastening method <ul style="list-style-type: none"> installation in media module slot | latched Yes |
| standards, specifications, approvals | |
| standard <ul style="list-style-type: none"> for FM for hazardous zone for safety / from CSA and UL | FM3611: Class 1, Division 2, Group A, B, C, D / T4, Class 1, Zone 2, Group IIC, T4 EN 60079-0: 2006, EN60079-15: 2005, II 3 G Ex nA II T4, KEMA 07 ATEX 0145 X UL 60950-1, CSA C22.2 No. 60950-1 |

| | |
|---|---|
| <ul style="list-style-type: none"> • for hazardous zone / from CSA and UL • for emitted interference • for interference immunity | UL 1604 and UL 2279-15 (Hazardous Location), CSA C22.2 No. 213-M1987, Class 1 / Division 2 / Group A, B, C, D / T4, Class 1 / Zone 2 / Group IIC / T4 EN 61000-6-4:2007 (Class A) EN 61000-6-2:2005 |
| certificate of suitability <ul style="list-style-type: none"> • CE marking • C-Tick • KC approval • CCC / for hazardous zone according to GB standard • CCC / for hazardous zone according to GB standard / as marking | EN 61000-6-2:2005, EN 61000-6-4:2007 Yes Yes Yes Yes Ex nA IIC T4 Gc |
| Marine classification association <ul style="list-style-type: none"> • French marine classification society (BV) | Yes |
| MTBF | 55 a |

further information / internet links

| | |
|--|---|
| internet link <ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx-Download-Manager • to website: Industry Online Support | http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com |
|--|---|

last modified: 5/28/2023 