

product type designation

MM992-4SFP

SCALANCE X accessory; Media module MM992-4SFP; 4x 100/1000 Mbit/s for SFP plug-in transceiver.



interfaces

number of electrical/optical connections / for network components or terminal equipment / maximum

4

number of electrical connections

- for SFP / plug-in

4

ambient conditions

ambient temperature

- during operation
- during storage
- during transport

0 ... 60 °C

-40 ... +85 °C

-40 ... +85 °C

relative humidity / at 25 °C / without condensation / during operation / maximum

95 %

protection class IP

IP20

design, dimensions and weights

design

Media module

width

120.3 mm

height

22.3 mm

depth

275.5 mm

net weight

0.3 kg

fastening method

latched

- installation in media module slot

Yes

standards, specifications, approvals

standard

- for safety / from CSA and UL
- for emitted interference
- for interference immunity

UL 60950-1, CSA C22.2 No. 60950-3

EN 61000-6-4 (Class A)

EN 61000-6-2

certificate of suitability

EN 61000-6-2:2005, EN 61000-6-4:2007

- CE marking

Yes

- C-Tick

Yes

- KC approval

Yes

- CCC / for hazardous zone according to GB standard

Yes

- E1 approval

No

Marine classification association

- French marine classification society (BV)

Yes

further information / internet-Links

Internet-Link

- to web page: selection aid TIA Selection Tool
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center

<http://www.siemens.com/tia-selection-tool>

<http://www.siemens.com/simatic-net>

<https://mall.industry.siemens.com>

<http://www.siemens.com/industry/infocenter>

- to website: Image database
- to website: CAX-Download-Manager
- to website: Industry Online Support

<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

7/7/2022 