

product type designation

MM992-4CU

SCALANCE X accessory; Media module MM992-4CU; 4x 1000 Mbit/s RJ45 ports, electrical; without securing collar.



interfaces

number of electrical/optical connections / for network components or terminal equipment / maximum	4
number of electrical connections	
for network components or terminal equipment / maximum	4
number of 10/100/1000 Mbit/s RJ45 ports	4
type of electrical connection	
for network components or terminal equipment	RJ45

ambient conditions

ambient temperature	
during operation	0 ... 60 °C
during storage	-40 ... +85 °C
during transport	-40 ... +85 °C
relative humidity / at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20

design, dimensions and weights

design	Media module
width	120.3 mm
height	22.3 mm
depth	275.5 mm
net weight	0.3 kg
fastening method	latched
installation in media module slot	Yes

standards, specifications, approvals

standard	
for safety / from CSA and UL	UL 60950-1, CSA C22.2 No. 60950-7
for emitted interference	EN 61000-6-4 (Class A)
for interference immunity	EN 61000-6-2
certificate of suitability	EN 61000-6-2:2005, EN 61000-6-4:2007
CE marking	Yes
C-Tick	Yes
KC approval	Yes
CCC / for hazardous zone according to GB standard	Yes
E1 approval	No
Marine classification association	
French marine classification society (BV)	Yes

further information / internet-Links

Internet-Link

- to web page: selection aid TIA Selection Tool
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAX-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>
<http://www.siemens.com/simatic-net>
<https://mall.industry.siemens.com>
<http://www.siemens.com/industry/infocenter>
<http://automation.siemens.com/bilddb>
<http://www.siemens.com/cax>
<https://support.industry.siemens.com>

last modified:

7/7/2022 