6GK7277-1AA10-0AA0

Data sheet



Compact Switch Module CSM 1277 for connecting SIMATIC S7-1200 and up to 3 further nodes to Industrial Ethernet with 10/100 Mbit/s; unmanaged switch, 4 RJ45 ports, ext. 24 V DC power supply LED diagnostics, S7-1200 module incl. electronic Equipment Manual on CD-ROM.

| product type designation | SCALANCE CSM 1277 |
|--|-------------------------------|
| transfer rate | |
| transfer rate | 10 Mbit/s, 100 Mbit/s |
| interfaces / for communication / integrated | |
| number of electrical connections | |
| for network components or terminal equipment | 4 |
| number of 100 Mbit/s SC ports | |
| for multimode | 0 |
| number of 1000 Mbit/s LC ports | |
| • for multimode | 0 |
| for single mode (LD) | 0 |
| interfaces / other | |
| number of electrical connections | |
| for power supply | 1 |
| type of electrical connection | |
| for power supply | 3-pole terminal block |
| supply voltage, current consumption, power loss | |
| type of voltage / 1 / of the supply voltage | DC |
| supply voltage / 1 / rated value | 24 V |
| power loss [W] / 1 / rated value | 1.6 W |
| supply voltage / 1 / rated value | 19.2 28.8 V |
| consumed current / 1 / maximum | 0.07 A |
| type of electrical connection / 1 / for power supply | 3-pole terminal block |
| product component / 1 / fusing at power supply input | Yes |
| fuse protection type / 1 / at input for supply voltage | 0.5 A / 60 V |
| ambient conditions | |
| ambient temperature | |
| during operation | 0 60 °C |
| during storage | -40 +70 °C |
| during transport | -40 +70 °C |
| relative humidity | 0.5.07 |
| at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP20 |
| design, dimensions and weights | |
| design | SIMATIC S7-1200 device design |
| width | 45 mm |
| height | 100 mm |
| depth | 75 mm |
| net weight | 0.15 kg |
| fastening method | |

| 35 mm top hat DIN rail mounting | Yes |
|---|--|
| wall mounting | Yes |
| S7-300 rail mounting | No |
| S7-1500 rail mounting | No |
| product functions / management, configuration, engineering | |
| product function | |
| multiport mirroring | No |
| product function / switch-managed | No |
| product functions / redundancy | |
| product function | |
| Parallel Redundancy Protocol (PRP)/operation in | Yes |
| the PRP-network | |
| Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) | No |
| standards, specifications, approvals | |
| standard | |
| • for FM | FM3611: Class 1, Divison 2, Group A, B, C, D / T, CL.1, Zone 2, GP. |
| • IOI I IVI | IIC, T Ta |
| for safety / from CSA and UL | UL 508, CSA C22.2 No. 142 |
| for emitted interference | EN 61000-6-4 (Class A) |
| for interference immunity | EN 61000-6-2 |
| MTBF | 273 y |
| reference code | |
| according to IEC 81346-2 | KF |
| • according to IEC 81346-2:2019 | KFE |
| standards, specifications, approvals / CE | |
| certificate of suitability / CE marking | Yes |
| standards, specifications, approvals / hazardous environn | nents |
| standard / for hazardous zone | EN 600079-15:2005, EN 600079-0:2006, II 3 G Ex nA II T4, KEMA 08 |
| | ATEX 0003 X |
| certificate of suitability | v. |
| CCC / for hazardous zone according to GB standard | Yes |
| standards, specifications, approvals / other | |
| certificate of suitability | EN 61000-6-2, EN 61000-6-4 |
| • C-Tick | Yes |
| KC approval | No |
| standards, specifications, approvals / marine classification | |
| Marine classification association | v. |
| American Bureau of Shipping Europe Ltd. (ABS) Formula marine alequification assists (DV) | Yes |
| French marine classification society (BV) Det Nerske Verites (DNV) | Yes |
| Det Norske Veritas (DNV)Germanische Lloyd (GL) | Yes No |
| Lloyds Register of Shipping (LRS) | Yes |
| Nippon Kaiji Kyokai (NK) | Yes |
| Polski Rejestr Statkow (PRS) | No |
| Royal Institution of Naval Architects (RINA) | No |
| further information / internet-Links | |
| Internet-Link | |
| to web page: selection aid TIA Selection Tool | http://www.siemens.com/tia-selection-tool |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |
| to website: Industry Mall | https://mall.industry.siemens.com |
| • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| to website: Image database | http://automation.siemens.com/bilddb |
| to website: CAx-Download-Manager | http://www.siemens.com/cax |
| to website: Industry Online Support | https://support.industry.siemens.com |
| security information | |
| security information | Siemens provides products and solutions with industrial security |
| | functions that support the secure operation of plants, solutions, |
| | machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' |
| | products and solutions undergo continuous development. Siemens |
| | recommends strongly that you regularly check for product updates. For |
| | the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and |
| | |

integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified:

9/17/2022