

SIEMENS

Product data sheet

6SL3201-0BE21-8AA0


Fig. similar

SINAMICS BRAKING RESISTOR R=75OHM
 P_RATED=375W P_MAX=7500W/12S/5% DUTY
 STANDALONE

Electrical resistance / of the braking resistor	75 Ω
Active power drawn / rated value	0.375 kW
• maximum	7.5 kW
Version, electrical connection / for power cable	Terminal block
Connectable conductor cross-section / for power cable	2.5 mm ²
Design of the temperature switch	Normally closed contact
Input voltage / of the temperature switch / for AC / maximum	250 V
Input current / of the temperature switch / for AC / maximum	2.5 A
Connectable conductor cross-section / on the temperature switch / maximum	2.5 mm ²
Design of electrical connection / of the protective conductor connection	Yes
Design of the protective conductor connection / to housing	M4 screw

Protection class IP	IP20
Width	175 mm
Height	345 mm
Depth	100 mm
Net weight	2.73 kg

Further information

[Information and download center for Industry Automation and Drives](#)

[Technical documentation \(Motion Control\)](#)

[Industry Mall \(online ordering system\)](#)

[Service & Support \(FAQs, manuals, operating instructions, certificates, characteristics, ...\)](#)

last change:

Mar 1, 2013