

### MLFB-Ordering data

6SL3211-1PB13-8AL0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
<b>Input</b>		<b>Power factor <math>\lambda</math></b>	0.85
<b>Number of phases</b>	1 / 3 AC	<b>Offset factor <math>\cos \varphi</math></b>	0.95
<b>Line voltage</b>	200 ... 240 V $\pm 10$ %	<b>Efficiency <math>\eta</math></b>	0.96
<b>Line frequency</b>	47 ... 63 Hz	<b>Sound pressure level (1m)</b>	56 dB
<b>Rated current (LO)</b>	9.60 / 5.50 A	<b>Power loss</b>	0.04 kW
<b>Rated current (HO)</b>	8.40 A	<b>Ambient conditions</b>	
<b>Output</b>		<b>Cooling</b>	Internal air cooling
<b>Number of phases</b>	3 AC	<b>Cooling air requirement</b>	0.005 m <sup>3</sup> /s
<b>Rated voltage</b>	230 V	<b>Installation altitude</b>	1000 m
<b>Rated power (LO)</b>	0.75 kW / 1.00 hp	<b>Ambient temperature</b>	
<b>Rated power (HO)</b>	0.55 kW / 0.75 hp	<b>Operation LO</b>	-5 ... 40 °C (23 ... 104 °F)
<b>Rated current (LO)</b>	4.20 A	<b>Operation HO</b>	-5 ... 50 °C (23 ... 122 °F)
<b>Rated current (HO)</b>	3.20 A	<b>Transport</b>	-40 ... 70 °C (-40 ... 158 °F)
<b>Max. output current</b>	6.40 A	<b>Storage</b>	-25 ... 55 °C (-13 ... 131 °F)
<b>Pulse frequency</b>	4 kHz	<b>Relative humidity</b>	
<b>Output frequency for vector control</b>	0 ... 200 Hz	<b>Max. operation</b>	95 % RH, condensation not permitted
<b>Output frequency for V/f control</b>	0 ... 550 Hz		

### Overload capability

#### Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

#### High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

SIEMENS

Data sheet for SINAMICS Power Module PM240-2

MLFB-Ordering data

6SL3211-1PB13-8AL0



Figure similar

Mechanical data		Connections	
Degree of protection	IP20	Line side	
Size	FSA	Version	Plug-in screw terminals
Net weight	2.00 kg	Conductor cross-section	1.00 ... 2.50 mm²
Width	126.0 mm	Motor end	
Height	238.0 mm	Version	Plug-in screw terminals
Depth	171.0 mm	Conductor cross-section	1.00 ... 2.50 mm²
		Max. motor cable length	
		Shielded	50 m
		Unshielded	100 m
Standards			
Compliance with standards		UL, cUL, CE, C-Tick (RCM), SEMI F47	
CE marking		Low-voltage directive 2006/95/EC	