

Specifications

Eaton 072367

Eaton Moeller® series RMQ16 Illuminated selector switch actuator, maintained/momentary, 45°, 25 x 25 mm, 3 positions, With thumb-grip, White, with VS anti-rotation tab, without light elements, With base, W2x4,6d; max. 30 V Q25LWK3R2-WS

General specifications

| | |
|-----------------------------|---|
| PRODUCT NAME | Eaton Moeller® series RMQ16 Illuminated selector switch actuator |
| CATALOG NUMBER | 072367 |
| EAN | 4015080723677 |
| PRODUCT LENGTH/DEPTH | 75 mm |
| PRODUCT HEIGHT | 25 mm |
| PRODUCT WIDTH | 25 mm |
| PRODUCT WEIGHT | 0.017 kg |
| CERTIFICATIONS | UL 508 UL Category Control No.: NKR CE CSA Class No.: 3211-03 CSA-C22.2 No. 14-05 IEC/EN 60947-5 UL CSA File No.: 46552 CSA IEC/EN 60947 UL File No.: E29184 |
| CATALOG NOTES | Filament bulb or LED needs to be ordered separately |
| MODEL CODE | Q25LWK3R2-WS |

Features & Functions

| | |
|-----------------------|----------------------|
| BEZEL COLOR | Black |
| BEZEL MATERIAL | Plastic |
| DESIGN | With thumb-grip |
| FITTED WITH: | VS anti-rotation tab |

General

| | |
|---|--|
| DEGREE OF PROTECTION | NEMA 1 |
| DEGREE OF PROTECTION (FRONT SIDE) | IP65 |
| LIFESPAN, MECHANICAL | 3,000,000 Operations |
| OPENING DIAMETER | 16 mm |
| OPERATING FREQUENCY | 1800 Operations/h |
| OPERATING TORQUE | 0.2 Nm |
| OVERVOLTAGE CATEGORY | III |
| POLLUTION DEGREE | 3 |
| PRODUCT CATEGORY | RMQ16 |
| RATED IMPULSE WITHSTAND VOLTAGE (UIMP) | 800 V AC |
| SIZE | Front dimensions: 25 × 25 mm |
| SUITABLE FOR | Illumination |
| SWITCHING ANGLE | 45 ° |
| TERMINAL CAPACITY | 0.5 - 1.0 mm ² |
| TERMINAL SIZE | 2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors 2.8 x 0.8 mm to DIN 46244, Blade terminal |
| TYPE | Illuminated selector switch actuator |

Ambient conditions, mechanical

| | |
|--------------------------|--|
| MOUNTING POSITION | As required |
| SHOCK RESISTANCE | 40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27 |

Climatic environmental conditions

| | |
|---|--|
| AMBIENT OPERATING TEMPERATURE - MIN | -25 °C |
| AMBIENT OPERATING TEMPERATURE - MAX | 60 °C |
| AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN | -25 °C |
| AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX | 40 °C |
| CLIMATIC PROOFING | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |

Electrical rating

| | |
|--------------------------------------|-------|
| RATED INSULATION VOLTAGE (UI) | 250 V |
|--------------------------------------|-------|

| | |
|---|------|
| RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX | 24 V |
|---|------|

Communication

| | |
|-----------------------------------|----|
| CONNECTION TO SMARTWIRE-DT | No |
|-----------------------------------|----|

Actuator

| | |
|-----------------------|-------|
| ACTUATOR COLOR | Black |
|-----------------------|-------|

| | |
|--------------------------|--|
| ACTUATOR FUNCTION | Spring-return Maintained/momentary Switching function latching |
|--------------------------|--|

| | |
|----------------------|--------|
| ACTUATOR TYPE | Toggle |
|----------------------|--------|

| | |
|-----------------------------------|---|
| NUMBER OF SWITCH POSITIONS | 3 |
|-----------------------------------|---|

Design verification

| | |
|---|-----|
| EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID | 0 W |
|---|-----|

| | |
|--|-----|
| HEAT DISSIPATION CAPACITY PDISS | 0 W |
|--|-----|

| | |
|--|-----|
| HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID | 0 W |
|--|-----|

| | |
|--|-----|
| RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) | 0 A |
|--|-----|

| | |
|---|-----|
| STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS | 0 W |
|---|-----|

| | |
|------------------------------------|--|
| 10.2.2 CORROSION RESISTANCE | Meets the product standard's requirements. |
|------------------------------------|--|

| | |
|---|--|
| 10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES | Meets the product standard's requirements. |
|---|--|

| | |
|---|--|
| 10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT | Meets the product standard's requirements. |
|---|--|

| | |
|---|--|
| 10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS | Meets the product standard's requirements. |
|---|--|

| | |
|---|----------------|
| 10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION | Please enquire |
|---|----------------|

| | |
|-----------------------|--|
| 10.2.5 LIFTING | Does not apply, since the entire switchgear needs to be evaluated. |
|-----------------------|--|

| | |
|---------------------------------|--|
| 10.2.6 MECHANICAL IMPACT | Does not apply, since the entire switchgear needs to be evaluated. |
|---------------------------------|--|

| | |
|---|--|
| 10.2.7 INSCRIPTIONS | Meets the product standard's requirements. |
| 10.3 DEGREE OF PROTECTION OF ASSEMBLIES | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 CLEARANCES AND CREEPAGE DISTANCES | Meets the product standard's requirements. |
| 10.5 PROTECTION AGAINST ELECTRIC SHOCK | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS | Is the panel builder's responsibility. |
| 10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS | Is the panel builder's responsibility. |
| 10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH | Is the panel builder's responsibility. |
| 10.9.3 IMPULSE WITHSTAND VOLTAGE | Is the panel builder's responsibility. |
| 10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL | Is the panel builder's responsibility. |
| 10.10 TEMPERATURE RISE | Not applicable. |
| 10.11 SHORT-CIRCUIT RATING | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 ELECTROMAGNETIC COMPATIBILITY | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 MECHANICAL FUNCTION | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Resources

CATALOGUES

[eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf](#)

[eaton-rmq-titan-brochure-br047004en-en-us.pdf](#)

DECLARATIONS OF CONFORMITY

[DA-DC-00004158.pdf](#)

[DA-DC-00004136.pdf](#)

DRAWINGS

[eaton-operating-switch-rmq16-dimensions.eps](#)

[eaton-operating-button-symbol-013.eps](#)

ECAD MODEL

[DA-CE-ETN.Q25LWK3R2-WS](#)

INSTALLATION INSTRUCTIONS

[IL04716016Z](#)

MCAD MODEL

[DA-CD-wahl_25](#)

[leuchtwahl_25.stp](#)

[DA-CS-wahl_25](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

