

Technical specifications

Data according to DIN 43751-1 and DIN 43751-2		7KT1 110		7KT1 120
Rated control supply voltage U_c	V AC	230		
Operating range	$\times U_c$	0.9 ... 1.15		
Rated frequency	Hz	45 ... 65		
Rated operational power P_s	VA	< 2		
Measuring range				
• Voltage	direct measurement	V AC	12 ... 600	--
• Current	direct measurement transformer measurement	A AC A AC	-- --	0.4 ... 20 direct 0.5 ... 1000/5
Display			3 LEDs red; height 10 mm	
• Voltage	voltage > 600 V voltage < 12 V	H H H --- ---	-- --	-- --
• Current	direct current > 20 A current transformer > 5 A direct current < 0.4 A current transformer < 0.1 A	-- -- -- --	H H H H H H -- -- -- -- -- --	-- --
Measuring cycle	/s	4 times		
Measuring accuracy	at 23 °C	%	±0.5 ± 1 digit	
Temperature influence		%/°C	±0.03	
Overload capability				
• Voltage	continuous short-time for 1 s	V V	720 780	-- --
• Current	continuous, direct continuous transformer short-time for 1 s, direct short-time for 1 s, transformer	A A A A	-- -- -- --	22 5.5 200 50
Electrical isolation				
• Clearances		mm	≥ 3	≥ 1.5
• Creepage distances in the device		mm	≥ 4.3	≥ 2.1
• Creepage distances on the printed board	printed boards not installed	mm	≥ 3.0	≥ 1.5
Test voltage	50 Hz, 1 min	kV	2.2	1.35
Terminals	+/- screw (Pozidriv)		1	
Conductor cross-sections	rigid, max. flexible with sleeve, min.	mm ² mm ²	1 x 6/2 x 4 0.75	
Permissible ambient temperature		°C	-10 ... +55	
Degree of protection			IP20	