| Description | Part-No. | technical | picture |
|-------------------------------------|-------------|--|---------|
| 10AX Plateswitch 1G/2W studio white | 8200-0-0132 | 8230-84 Busch-iDock 1 Complete set, Ready-to-install complete set for mono operation. Consisting of Busch-iDock 8218 U (iPod*/iPhone* docking station for models with a dock connector, The music playback takes place through Busch - DigitalRadio, with charging function of the connected device), FT DigitalRadio 8215 U, speaker insert 8223 U, cover plate for Busch-iDock, cover plate for FT DigitalRadio, cover plate for speaker insert, 3gang future ® linear cover frame, Rated voltage: 230 V~, +10 % / - 10 %, Rated frequency: 50 Hz, Protection class (Device): IP 20, Installation depth: 34 mm, it can be converted to Concept bs range by using 3x AC503 and 2x AC5103 or AC5103-S | |

| 10AX Plateswitch 2G/2W studio white | 8200-0-0142 | 8218 U Busch-iDock, iPod*/iPhone* docking station for models with a dock connector. The music playback takes place through Busch - DigitalRadio 8215 U. Can be used as a music source for Busch-AudioWorld ® systems. With charging function of the contacted device. With IR receiver to control the contacted device via the Apple* Remote.Acknowledgement of the received IR commands through the integrated LED. With control function for Busch-DigitalRadio 8215 U. With AUX input (3.5 mm stereo jack) for additional playback devices. Can be installed as 1gang and in multiple combinations. *Apple, iPod, and iPhone are registered trademarks of Apple Inc. Rated voltage: 230 V~, +10 % / -10 %, Rated frequency: 50 Hz, Protection class (Device): IP 20, Installation depth: 34 mm |
|---------------------------------------|-------------|---|
| 10AX Plateswitch interm. Studio white | 8200-0-0135 | 8254-84 Cover plate For Busch-iDock 8218 U. future ® linear, picture shows complete with frame, frame needs to be ordered separately |