

836 Pressure Controls - General Industrial

[836-C7A](#)



Representative Rendering, Not The Actual Product

836 Pressure Controls - General Industrial, Device Style C, External Copper Alloy Bellows, Type 1 Enclosure , No Modifications

Product Details

Note	
Modified Industrial Control Options are Available. Email to RADBQUOTE@RA.ROCKWELL.COM	-See "OPTIONS" Section Below: -LED option -Custom Factory Installed Modification text field
PRESSURE CONTROLS	
Hazardous Location Product Required?	No
Device Style	Device Style C, External Copper Alloy Bellows
Custom Trip or Reset Setting	Default Factory Setting
Pressure Specifications	150 psi.
Adjustable Differential psi (Approximate Mid-Range Values)	2
Maximum Line Pressure	300
ENCLOSURE	
Enclosure Type	Type 1 Enclosure
MODIFICATIONS	
Factory Modifications	No Modifications
OPTIONS	
Option	No LED pilot option
NOTES	
Note====>	Standard contact block - Single-pole, double-throw, snap action. Non-inductive ratings, 5 A, 240V. 3 A, 600V. Control circuit ratings AC - 125 VA, 24...600V. DC - 57.5 VA, 115...230V.

Supporting Documentation and Downloads

- [Photo](#)
- [Technical Data](#)
- [Enclosure Dimensions](#)