SQUARE 11





Plug in relay, Type KP, tubular, 1 HP at 277 VAC, 10A resistive at 120 VAC, 11 pin, 3PDT, 3 NO, 3 NC, 12 VDC coil, light

8501KPDR13P14V51

① To be discontinued

! To be discontinued on: Aug 15, 2024

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 96.99 USD

Main

product range	8501K	
product type	Relay	
Relay Type	General purpose	
mounting type	Socket	
contact composition	3PDT	
[Uc] control circuit voltage	12 V DC	
pilot light	Indicator light relay energised LED	
manual operator	Without test button	

Complementary

horsepower rating	1 hp 277 V AC
	0.33 hp 120 V AC
breaking capacity	3 A 120 V AC inductive control circuit UL 508
	1.5 A 240 V AC inductive control circuit UL 508
	10 A 277 V AC resistive control circuit UL 508
	10 A 30 V DC resistive control circuit UL 508
maximum switching voltage	300 V AC
	30 V DC
contact material	Silver alloy (AgNi)
operating time	20 ms - pick-up
	20 ms - drop-out
shape of pins	Tubular
for use with	8501NR62
	8501NR61

Environment

ambient temperature range - operational	-4055 °C (-40131 °F)
product certifications	UL Listed UL Recognized CSA CE
Height	2 66 in (67 56 mm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Width	1.4 in (35.6 mm)
Depth	1.4 in (35.6 mm)

Ordering and shipping details

Category	US10CP221141	
Discount Schedule	0CP2	
GTIN	785901736288	
Returnability	No	
Country of origin	CN	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.0000000000 in (7.62 cm)
Package 1 Width	1.600 in (4.064 cm)
Package 1 Length	1.600 in (4.064 cm)
Package 1 Weight	3.200 oz (90.718 g)



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Reach Free Of Svhc



Rohs Exemption Information


Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California Proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Dimensions Drawings

Approximate Dimensions



Product data sheet 8501KPDR13P14V51

Connections and Schema

Connections and Wiring Diagrams

8501KP13••• /12 6 7

NEMA IEC