



Plug in relay, Type R, hermetically sealed miniature, 5A resistive at 240 VAC, 14 blade, 4PDT, 4 NO, 4 NC, 12 VDC coil

8501RSD34V51

Main

Product Range	8501R
Product Type	Miniature Relay
Relay Type	I ow voltage

Complementary

Mounting Type	Socket	
Contact Composition	4PDT	
[Uc] Control Circuit Voltage	12 V DC	
Pilot Light	No indicator	
Manual Operator	Without test button	
Horsepower Rating	Not rated	
Breaking Capacity	5 A 120 V AC resistive control circuit UL 508 5 A 240 V AC resistive control circuit UL 508 5 A 30 V DC resistive control circuit UL 508	
Maximum Switching Voltage	30 V DC 240 V AC	
Contact Material	Hermetically sealed silver tin oxide	
Operating Time	20 ms - pick-up 20 ms - drop-out	
Shape Of Pins	Spade	
For Use With	8501NR45	
Height	1.16 in (29.4 mm)	
Width	0.91 in (23.1 mm)	
Depth	1.53 in (38.9 mm)	

Environment

Ambient Temperature Range - Operational	-40131 °F (-4055 °C)
Product Certifications	UL listed
	UL recognized
	CSA
	CE

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Package 1 Height	1.40 in (3.556 cm)	
Package 1 Width	2.00 in (5.08 cm)	
Package 1 Length	1.30 in (3.302 cm)	
Package 1 Weight	1.60 oz (45.359 g)	

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

Reach Free Of Svhc	
Toxic Heavy Metal Free	
Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration