

# Specifications

## Eaton 087232

Eaton Moeller® series RMQ16 Illuminated pushbutton actuator, white, maintained Q25LTR-WS

### General specifications

<b>PRODUCT NAME</b>	Eaton Moeller® series RMQ16 Illuminated pushbutton actuator
<b>CATALOG NUMBER</b>	087232
<b>EAN</b>	4015080872320
<b>PRODUCT LENGTH/DEPTH</b>	59 mm
<b>PRODUCT HEIGHT</b>	25 mm
<b>PRODUCT WIDTH</b>	25 mm
<b>PRODUCT WEIGHT</b>	0.011 kg
<b>CERTIFICATIONS</b>	CSA Class No.: 3211-03 IEC/EN 60947 UL Category Control No.: NKCR IEC/EN 60947-5 UL File No.: E29184 CE CSA File No.: 46552 CSA-C22.2 No. 14-05 UL UL 508 CSA
<b>CATALOG NOTES</b>	Filament bulb or LED needs to be ordered separately
<b>MODEL CODE</b>	Q25LTR-WS

## Features & Functions

<b>BEZEL COLOR</b>	Black
<b>BEZEL MATERIAL</b>	Plastic
<b>DESIGN</b>	Flat
<b>INSCRIPTION</b>	Blank

## General

<b>DEGREE OF PROTECTION</b>	IP65 NEMA 1
<b>DEGREE OF PROTECTION (FRONT SIDE)</b>	IP65 NEMA 1
<b>LIFESPAN, MECHANICAL</b>	30,000,000 Operations
<b>OPENING DIAMETER</b>	16 mm
<b>OPERATING FREQUENCY</b>	1800 Operations/h
<b>OVERVOLTAGE CATEGORY</b>	III
<b>POLLUTION DEGREE</b>	3
<b>PRODUCT CATEGORY</b>	RMQ16
<b>RATED IMPULSE WITHSTAND VOLTAGE (UIMP)</b>	800 V AC
<b>SIZE</b>	Front dimensions: 25 x 25 mm
<b>SUITABLE FOR</b>	Illumination
<b>TERMINAL CAPACITY</b>	0.5 - 1.0 mm <sup>2</sup>
<b>TERMINAL SIZE</b>	2.8 x 0.8 mm to DIN 46244, Blade terminal 2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors
<b>TYPE</b>	Illuminated pushbutton actuator

## Ambient conditions, mechanical

<b>MOUNTING POSITION</b>	As required
<b>SHOCK RESISTANCE</b>	Mechanical, According to IEC/EN 60068-2-27 40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms

## Climatic environmental conditions

<b>AMBIENT OPERATING TEMPERATURE - MIN</b>	-25 °C
<b>AMBIENT OPERATING TEMPERATURE - MAX</b>	60 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN</b>	25 °C
<b>AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX</b>	40 °C
<b>CLIMATIC PROOFING</b>	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

## Electrical rating

<b>RATED INSULATION VOLTAGE (UI)</b>	250 V
--------------------------------------	-------

<b>RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX</b>	24 V
---	------

## Communication

<b>CONNECTION TO SMARTWIRE-DT</b>	No
-----------------------------------	----

## Actuator

<b>ACTUATING FORCE</b>	4 N
------------------------	-----

<b>ACTUATOR COLOR</b>	White
-----------------------	-------

<b>ACTUATOR FUNCTION</b>	Maintained Switching function latching
--------------------------	---

## Design verification

<b>EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID</b>	0 W
---	-----

<b>HEAT DISSIPATION CAPACITY PDISS</b>	0 W
--	-----

<b>HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID</b>	0 W
--	-----

<b>RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)</b>	0 A
--	-----

<b>STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS</b>	0 W
---	-----

<b>10.2.2 CORROSION RESISTANCE</b>	Meets the product standard's requirements.
------------------------------------	--

<b>10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES</b>	Meets the product standard's requirements.
---	--

<b>10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT</b>	Meets the product standard's requirements.
---	--

<b>10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS</b>	Meets the product standard's requirements.
---	--

<b>10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION</b>	Please enquire
---	----------------

<b>10.2.5 LIFTING</b>	Does not apply, since the entire switchgear needs to be evaluated.
-----------------------	--

<b>10.2.6 MECHANICAL IMPACT</b>	Does not apply, since the entire switchgear needs to be evaluated.
---------------------------------	--

<b>10.2.7 INSCRIPTIONS</b>	Meets the product standard's requirements.
----------------------------	--

<b>10.3 DEGREE OF PROTECTION OF ASSEMBLIES</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.4 CLEARANCES AND CREEPAGE DISTANCES</b>	Meets the product standard's requirements.
<b>10.5 PROTECTION AGAINST ELECTRIC SHOCK</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS</b>	Does not apply, since the entire switchgear needs to be evaluated.
<b>10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS</b>	Is the panel builder's responsibility.
<b>10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS</b>	Is the panel builder's responsibility.
<b>10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH</b>	Is the panel builder's responsibility.
<b>10.9.3 IMPULSE WITHSTAND VOLTAGE</b>	Is the panel builder's responsibility.
<b>10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL</b>	Is the panel builder's responsibility.
<b>10.10 TEMPERATURE RISE</b>	Not applicable.
<b>10.11 SHORT-CIRCUIT RATING</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.12 ELECTROMAGNETIC COMPATIBILITY</b>	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
<b>10.13 MECHANICAL FUNCTION</b>	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Resources

CATALOGUES	<a href="#">eaton-rmq-titan-brochure-br047004en-en-us.pdf</a>
	<a href="#">eaton-pushbuttons-signal-towers-sensors-assortment-overview-catalog-ca047003en-en-us.pdf</a>
DECLARATIONS OF CONFORMITY	<a href="#">DA-DC-00004136.pdf</a>
	<a href="#">DA-DC-00004158.pdf</a>
DRAWINGS	<a href="#">eaton-operating-pushbutton-rmq16-dimensions-002.eps</a>
	<a href="#">116C076</a>
ECAD MODEL	<a href="#">ETN.087232.edz</a>
INSTALLATION INSTRUCTIONS	<a href="#">IL04716016Z</a>
MCAD MODEL	<a href="#">DA-CS-druck_25</a>
	<a href="#">leuchtdruck_25.stp</a>
	<a href="#">DA-CD-druck_25</a>

---

PROJECT NAME:

---

PROJECT NUMBER:

---

PREPARED BY:

---

DATE:

---



### Eaton Corporation plc

Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

