



PRODUCT-DETAILS

8755  
20A,REC,4P5W,SE,125/250V



Product image  
not available

General Information	
Extended Product Type	8755
Product ID	7TAA057320R0022
Catalog Description	20A,REC,4P5W,SE,125/250V
Long Description	Standard Ever-Lok 20 Amp Receptacle, 4 Pole 5 Wire, 125/250V

Ordering	
UPC	708917312772
Country of Origin	United States
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 EA
Package Level 1 Width	95.25 mm 3.75 in
Package Level 1 Height	69.85 mm 2.75 in

Package Level 1 Depth / Length	139.7 mm 5.5 in
--------------------------------	--------------------

Additional Information

Application	General Industrial: Lighting Connections, Indoor Welding Stations, Machinery/Tool Connections, Power Distributions Panels, Convenience Power, Battery Charging Equipment
Brand / Label	Russellstoll
Current Rating	20 A
Effective Date	20061004
Material	Heavy gauge steel plated receptacle housing
Number of Conductors	5
Number of Poles	4P
Product Name	Cylindrical multicontact connectors
Product Type	DuraTite & Ever-Lok Locking Connections
Special Functions	Automatic Locking, Positive Grounding by means of phosphor-bronze ground straps, Dust Proof
Voltage Rating	250 V

Certificates and Declarations

Data Sheet, Technical Information	8755
-----------------------------------	------

External Classifications and Standards

ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121404
IDEA Granular Category Code (IGCC)	4528 >> Electrical sleeves

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Pin & Sleeve Connectors



Product image  
not available