



Busbar system Busbar center-to-center spacing 60 mm Device adapter,
Width: 45 mm Bar thickness: 5.10 mm+TT profile for circuit breaker,
Contactor Overload relay, Motor feeders S00, S0, Length 182 mm with 1
DIN rail 35 mm, up to 25 A

Model	
product brand name	SENTRON
product designation	Device adapter
design of the product	Accessories
operational current at AC rated value	25 A
number of mounting rails	1
Mechanical Design	
height	182 mm
width of the adapter	45 mm
depth	60 mm
thickness of the busbar	
• minimum	5 mm
busbar center-to-center spacing	60 mm
net weight	167.5 g
General Product Approval	



[Confirmation](#)



Declaration of Conformity	Test Certificates	Marine / Shipping
 EG-Konf.		 Miscellaneous
	 Special Test Certificate	 ABS
		 PRS

Marine / Shipping	other
 RINA	Miscellaneous Confirmation

Further information
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1251-5DM07>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8US1251-5DM07>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1251-5DM07

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



