

PE terminal 2 screw terminals green-yellow, 8mm, Sz. 6



Model	
product brand name	ALPHA
product designation	PE through-type terminal
General technical data	
insulation material	thermoplastic
terminal contact spacing	8 mm
Protection class	
combustibility class according to UL 94	V2
Appearance	
color	green-yellow
Product details	
product component required end cover plate	No
Number	
number of terminal levels	2
number of terminal points per terminal level	1
Connections	
stripped length	11 mm
connectable conductor cross-section solid	
• maximum	6 mm ²
connectable conductor cross-section stranded	
• maximum	6 mm ²
connectable conductor cross-section finely stranded	
• with core end processing maximum	6 mm ²
• without core end processing maximum	6 mm ²
tightening torque with screw-type terminals	
• minimum	0.8 N·m
• maximum	0.8 N·m
type of connection	
• 1	screw-type terminal
• 2	screw-type terminal
position of the terminal	lateral
Mechanical Design	
height with lowest-profile installation	33 mm
length	51 mm
fastening method	DIN rail 35 mm
net weight	29.1 g
material of the insulating body	Thermoplastic
Environmental conditions	
ambient temperature during operation	
• minimum	-25 °C

• maximum

55 °C

General Product Approval

Declaration of
Conformity

Test Certificates



[Confirmation](#)



[Miscellaneous](#)

other

[Environmental Con-
firmations](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1011-1PH00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WA1011-1PH00>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1PH00

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



