SIEMENS

Data sheet 8WA1011-1SF30



Fuse terminal Screw terminal for inch fuse link 1/4'X1' and 1/4'X1 1/4'

product brand name ALPHA type of light source as defect indicator without design of the fuse link clesign of the holder without Coneral technical data insulation material terminal contact spacing 10 mm Supply voltage operating voltage rated value type of voltage for supply of the defect indicator Protection class combustibility class according to UL 94 Alan circuit operational current rated value porational current rated value Product datails product component required end cover plate No Number number of terminal levels Connectable conductor cross-section solid e-minimum e-maximum connectable conductor cross-section stranded e-maximum connectable conductor cross-section finely stranded e-maximum connectable conductor cross-sectio		
Type of light source as defect indicator without design of the fuse link others design of the sub elink others without Ceneral technical data Insulation material terminal contact spacing 10 mm Supply voltage Operating voltage and value 250 V type of voltage for supply of the defect indicator others Protection class coording to UL 94 Other Main circuit operational current rated value 6.3 A Appearance Coor miscellaneous Product details product component required end cover plate No Numbor number of terminal levels 1 Connectable conductor cross-section solid • minimum 1 mm² • maximum 1 mm² • maximum 1.5 mm² • maximum 1.5 mm² • with core end processing maximum 1.5 mm² • vith core end processing maximum 1.5 mm² • ye with core end processing maximum 1.5 mm² • ye with core end processing maximum 1.5 mm² • postion the terminal levels 1 connectable conductor cross-section finely stranded • with core end processing maximum 1.5 mm² • ye with core end processing maximum 1.5 mm² • ye with core end processing maximum 1.5 mm² • ye of connectable conductor cross-section finely stranded • with core end processing maximum 1.5 mm² • ye of connectable conductor cross-section finely stranded • with core end processing maximum 1.5 mm² • ye of connectable conductor cross-section finely stranded • with core end processing maximum 1.5 mm² • ye of connectable conductor cross-section finely stranded • with core end processing maximum 1.5 mm² • ye of connectable conductor cross-section finely stranded • with core end processing maximum 1.5 mm² • ye of connectable conductor cross-section finely stranded • with core end processing maximum 1.5 mm² • ye of connectable conductor cross-section finely stranded • with core end processing maximum 1.5 mm² • ye of connectable conductor cross-section finely stranded • with core end processing maximum 1.5 mm² • ye of connectable conductor cross-section finely stranded • with core end processing maximum 1.5 mm² • ye of connectable conductor cross-section finely stranded • ye with core end processing m	Model	
design of the fuse link design of fuse holder without General technical data insulation material terminal contact spacing 10 mm Supply voltage or supply of the defect indicator others Protection class combustibility class according to UL 94 Other Main circuit operating voltage rated value 6.3 A Appearance color miscellaneous Product details product component required end cover plate No No Number number of terminal levels 1 Connectable conductor cross-section solid • minimum 1 mm² • maximum 1.5 mm² connectable conductor cross-section finely stranded • maximum 1.5 mm² type of connection • with core end processing minimum 0.75 mm² type of connection • 1 • 2 position of the terminal levels 1 Connectable conductor cross-section finely stranded • with core end processing minimum 0.75 mm² type of connection • 1 • 2 position of the terminal levels 1 Mechanical Design height with lowest-profile installation 42 mm length 657 mm fastening method DIN rail 35 mm	·	
design of fuse holder Ceneral technical data insulation material terminal contact spacing Supply voitage operating voitage rated value type of voitage for supply of the defect indicator type of voitage for supply of the defect indicator operating voitage for supply of the defect indicator Protection class combustibility class according to UL 94 Main circuit operational current rated value 6.3 A Appearance color miscellaneous Product details product component required end cover plate No No No No Connections connectable conductor cross-section solid minimum maximum maximum maximum connectable conductor cross-section stranded maximum connectable conductor cross-section finely stranded minimum with core end processing minimum with core end processing miximum with core end processing miximum with core end processing miximum vitye of connection 1 screw-type terminal evel 2 consistion of the terminal Mechanical Dosign fiestening method DIN rail 35 mm		
Insulation material Insulation Insulati	design of the fuse link	others
insulation material thermical terminal contact spacing 10 mm Supply voltage or parting voltage rated value 250 V type of voltage for supply of the defect indicator others Protection class combustibility class according to UL 94 Other Main circuit operational current rated value 6.3 A Appearance color miscellaneous Product details product component required end cover plate No Number number of terminal levels 1 Connectable conductor cross-section solid minimum 1 mm² maximum 1.5	design of fuse holder	without
terminal contact spacing 10 mm Supply voltage operating voltage rated value 250 V type of voltage for supply of the defect indicator others Protection class combustibility class according to UL 94 Other Main circuit operational current rated value 6.3 A Appearance color miscellaneous Product details product component required end cover plate No Number number of terminal levels 1 connectable conductor cross-section solid inimimum 1 mm² maximum 1 mm² onnectable conductor cross-section stranded maximum 1.5 mm² connectable conductor cross-section finely stranded with core end processing minimum 0.75 mm² with core end processing minimum 0.75 mm² type of connection very connectable conductor cross-section finely stranded with core end processing minimum 0.75 mm² type of connection very connectable conductor cross-section finely stranded with core end processing minimum 0.75 mm² type of connection very core end processing minimum 0.75 mm² type of connection very core end processing minimum 0.75 mm² type of connection very core end processing minimum 0.75 mm² type of connection very core end processing minimum 0.75 mm² type of connection very core end processing minimum 0.75 mm² type of connection very core end processing minimum 0.75 mm² type of connection very core end processing minimum 0.75 mm² type of connection very core end processing minimum 0.75 mm² type of connection very core end processing minimum 0.75 mm² type of connection very core end processing minimum 0.75 mm² very core end processing minimu	General technical data	
Supply voltage operating voltage rated value type of voltage for supply of the defect indicator Protection class combustibility class according to UL 94 Main circuit operational current rated value Appearance color miscellaneous Product details product component required end cover plate No Number number of terminal levels connectable conductor cross-section solid minimum maximum maximum monaximum monaximum connectable conductor cross-section finely stranded miximum monaximum monaximum numerone one conductor cross-section finely stranded miximum monaximum numerone one processing minimum monaximum numerone one one processing minimum numerone one difference one processing minimum monaximum numerone one one processing minimum numerone one one one one one one one one one	insulation material	thermoplastic
operating voltage rated value 250 V type of voltage for supply of the defect indicator others Protection class combustibility class according to UL 94 Other Main circuit operational current rated value 6.3 A Appearance color miscellaneous Product dotalls product component required end cover plate No Number number of terminal levels 1 Connections connectable conductor cross-section solid • minimum 1 mm² • maximum 1 mm² • maximum 1.5 mm² connectable conductor cross-section stranded • maximum 0.75 mm² • with core end processing minimum 0.75 mm² • with core end processing maximum 1.5 mm² type of connection • 1 screw-type terminal • 2 screw-type terminal position of the terminal Mechanical Design Mechanical Design fastening method DIN rail 35 mm	terminal contact spacing	10 mm
type of voltage for supply of the defect indicator others Protection class combustibility class according to UL 94 Other Main circuit operational current rated value 6.3 A Appearance color miscellaneous Product details product component required end cover plate No Number number of terminal levels 1 Connections connectable conductor cross-section solid minimum 1 mm² maximum 1 mm² maximum 1.5 mm² connectable conductor cross-section stranded maximum 0.75 mm² with core end processing minimum 0.75 mm² with core end processing maximum 1.5 mm² type of connection e) in screw-type terminal ye of connection screw-type terminal lateral Mechanical Design Height with lowest-profile installation 42 mm fastening method DIN rail 35 mm	Supply voltage	
Protection class combustibility class according to UL 94 Main circuit Operational current rated value Appearance color miscellaneous Product details product component required end cover plate No Number number of terminal levels Connections connectable conductor cross-section solid • minimum 1 mm² • maximum 1 mm² connectable conductor cross-section stranded • maximum 1.5 mm² connectable conductor cross-section finely stranded • with core end processing minimum 0.75 mm² with core end processing miximum 1.5 mm² type of connection • 1 screw-type terminal • 1 screw-type terminal height with lowest-profile installation 42 mm length 57 mm fastening method DIN rail 35 mm	operating voltage rated value	250 V
combustibility class according to UL 94 Main circuit operational current rated value Appearance color miscellaneous Product details product component required end cover plate No Number number of terminal levels connectable conductor cross-section solid minimum maximum moentable conductor cross-section stranded maximum moentable conductor cross-section finely stranded minimum moentable conductor cross-section fin	type of voltage for supply of the defect indicator	others
Main circuit operational current rated value Appearance color miscellaneous Product details product component required end cover plate No Number number of terminal levels Connections connectable conductor cross-section solid e minimum e maximum 1 mm² connectable conductor cross-section stranded e maximum 1.5 mm² connectable conductor cross-section finely stranded e with core end processing minimum e with core end processing maximum 1.5 mm² type of connection e1 screw-type terminal e2 screw-type terminal position of the terminal Mcchanical Design Height with lowest-profile installation length fastening method DIN rail 35 mm	Protection class	
operational current rated value 6.3 A Appearance color miscellaneous Product details product component required end cover plate No Number number of terminal levels 1 Connectable conductor cross-section solid • minimum 1 mm² • maximum 1 mm² connectable conductor cross-section stranded • maximum connectable conductor cross-section finely stranded • with core end processing minimum 0.75 mm² type of connection • 1 screw-type terminal • 2 screw-type terminal • 2 screw-type terminal • 2 position of the terminal Mechanical Design height with lowest-profile installation 42 mm length fastening method DIN rail 35 mm	combustibility class according to UL 94	Other
Appearance color miscellaneous Product details product component required end cover plate No Number number of terminal levels 1 Connectable conductor cross-section solid	Main circuit	
color miscellaneous Product details product component required end cover plate No Number number of terminal levels 1 Connections connectable conductor cross-section solid • minimum • maximum • maximum connectable conductor cross-section stranded • maximum connectable conductor cross-section stranded • maximum connectable conductor cross-section finely stranded • with core end processing minimum • with core end processing maximum type of connection • 1 • 2 position of the terminal lateral Mechanical Design height with lowest-profile installation length fastening method DIN rail 35 mm	operational current rated value	6.3 A
Product component required end cover plate No Number number of terminal levels 1 Connections connectable conductor cross-section solid • minimum • maximum connectable conductor cross-section stranded • maximum connectable conductor cross-section stranded • maximum connectable conductor cross-section finely stranded • with core end processing minimum • with core end processing maximum type of connection • 1 • 2 screw-type terminal • 2 position of the terminal Mechanical Design height with lowest-profile installation 42 mm length fastening method DIN rail 35 mm	Appearance	
product component required end cover plate No Number number of terminal levels Connections connectable conductor cross-section solid • minimum • maximum connectable conductor cross-section stranded • maximum connectable conductor cross-section stranded • maximum connectable conductor cross-section finely stranded • with core end processing minimum • with core end processing maximum type of connection • 1 • 2 position of the terminal Mechanical Design height with lowest-profile installation length fastening method DIN rail 35 mm	color	miscellaneous
Number number of terminal levels Connections connectable conductor cross-section solid • minimum • maximum connectable conductor cross-section stranded • maximum connectable conductor cross-section stranded • maximum connectable conductor cross-section finely stranded • with core end processing minimum • with core end processing maximum type of connection • 1 • 2 position of the terminal Mechanical Design height with lowest-profile installation length fastening method 1 mm² 1 mm²	Product details	
number of terminal levels Connections connectable conductor cross-section solid • minimum • maximum connectable conductor cross-section stranded • maximum connectable conductor cross-section stranded • maximum connectable conductor cross-section finely stranded • with core end processing minimum • with core end processing maximum type of connection • 1 • 2 position of the terminal Mechanical Design height with lowest-profile installation length fastening method DIN rail 35 mm	product component required end cover plate	No
Connectable conductor cross-section solid	Number	
connectable conductor cross-section solid • minimum • maximum connectable conductor cross-section stranded • maximum connectable conductor cross-section stranded • maximum connectable conductor cross-section finely stranded • with core end processing minimum • with core end processing maximum 1.5 mm² type of connection • 1 • 2 screw-type terminal • 2 screw-type terminal position of the terminal Mechanical Design height with lowest-profile installation length fastening method DIN rail 35 mm	number of terminal levels	1
 minimum maximum 1 mm² connectable conductor cross-section stranded maximum maximum tonnectable conductor cross-section finely stranded with core end processing minimum with core end processing maximum type of connection 1 screw-type terminal 2 screw-type terminal position of the terminal lateral Mechanical Design height with lowest-profile installation length fastening method DIN rail 35 mm 	Connections	
 maximum connectable conductor cross-section stranded maximum connectable conductor cross-section finely stranded with core end processing minimum with core end processing maximum type of connection 1 screw-type terminal 2 screw-type terminal position of the terminal lateral Mechanical Design height with lowest-profile installation fastening method DIN rail 35 mm 	connectable conductor cross-section solid	
connectable conductor cross-section stranded • maximum connectable conductor cross-section finely stranded • with core end processing minimum • with core end processing maximum 1.5 mm² type of connection • 1 • 2 screw-type terminal • 2 screw-type terminal position of the terminal Mechanical Design height with lowest-profile installation length fastening method DIN rail 35 mm	• minimum	1 mm ²
maximum connectable conductor cross-section finely stranded with core end processing minimum with core end processing maximum 1.5 mm² type of connection 1 screw-type terminal 2 screw-type terminal position of the terminal Mechanical Design height with lowest-profile installation length fastening method 1.5 mm² 1.5 m	• maximum	1 mm²
connectable conductor cross-section finely stranded • with core end processing minimum • with core end processing maximum 1.5 mm² type of connection • 1 • 2 screw-type terminal • 2 position of the terminal Mechanical Design height with lowest-profile installation length fastening method DIN rail 35 mm	connectable conductor cross-section stranded	
 with core end processing minimum with core end processing maximum type of connection 1 screw-type terminal 2 screw-type terminal position of the terminal lateral Mechanical Design height with lowest-profile installation length fastening method DIN rail 35 mm 	• maximum	1.5 mm ²
with core end processing maximum type of connection 1 screw-type terminal 2 screw-type terminal position of the terminal Mechanical Design height with lowest-profile installation length fastening method 1.5 mm² 1.5 mm² 1.5 mm² 42 mm lateral DIN rail 35 mm	connectable conductor cross-section finely stranded	
type of connection	 with core end processing minimum 	0.75 mm ²
screw-type terminal screw-type terminal position of the terminal Mechanical Design height with lowest-profile installation length fastening method DIN rail 35 mm	 with core end processing maximum 	1.5 mm²
● 2 screw-type terminal position of the terminal lateral Mechanical Design height with lowest-profile installation 42 mm length 57 mm fastening method DIN rail 35 mm	type of connection	
position of the terminal lateral Mechanical Design height with lowest-profile installation 42 mm length 57 mm fastening method DIN rail 35 mm	• 1	screw-type terminal
Mechanical Design height with lowest-profile installation 42 mm length 57 mm fastening method DIN rail 35 mm	• 2	screw-type terminal
height with lowest-profile installation 42 mm length 57 mm fastening method DIN rail 35 mm	position of the terminal	lateral
length 57 mm fastening method DIN rail 35 mm	Mechanical Design	
fastening method DIN rail 35 mm	height with lowest-profile installation	42 mm
	length	57 mm
material of the insulating body Thermoplast	fastening method	DIN rail 35 mm
	material of the insulating body	Thermoplast

General Product Approval

Declaration of Conformity

other



Confirmation







Confirmation

other Environment

<u>Miscellaneous</u> <u>Environmental Confirmations</u>

Further information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1011-1SF30

 $Service \& Support \ (Manuals, \ Certificates, \ Characteristics, \ FAQs, ...)$

https://support.industry.siemens.com/cs/ww/en/ps/8WA1011-1SF30

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1SF30

CAx-Online-Generator http://www.siemens.com/cax

Tender specifications

http://www.siemens.com/specifications