

LED, Base BA 15d, blue, 230 V AC, accessory for signaling columns, with diameters 50 mm and 70 mm



product brand name		SIRIUS	
product designation		LED	
General technical data			
type of voltage of the operating voltage		AC	
operating voltage			
• 1 at AC at 50 Hz rated value		230 V	
• 1 at AC at 60 Hz rated value		230 V	
relative positive tolerance of the operating voltage		10 %	
relative negative tolerance of the operating voltage		-15 %	
reference code according to EN 61346-2		P	
Lamp			
type of light source		LED	
light intensity		0.25 cd	
socket design		BA 15d	
Enclosure			
height		45 mm	
width		20 mm	
outer diameter of the signal column element		70 mm	
color		blue	
Ambient conditions			
ambient temperature during operation		-20 ... +60 °C	
Certificates/ approvals			
General Product Approval		EMC	Declaration of Conformity
			other

[Confirmation](#)



[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WD4458-6XF>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD4458-6XF>


Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WD4458-6XF>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD4458-6XF&lang=en

-P



last modified:

12/23/2020 