

Terminal, spring-loaded terminal, 3 clamping points, PE/PEN terminal, 2.5 mm², green-yellow



Model	
product brand name	ALPHA
product designation	PE through-type terminal
General technical data	
insulation material	thermoplastic
terminal contact spacing	5.2 mm
Protection class	
combustibility class according to UL 94	V0
Appearance	
color	miscellaneous
Product details	
product component required end cover plate	Yes
Number	
number of terminal levels	1
number of terminal points per terminal level	3
Connections	
connectable conductor cross-section solid	
• minimum	0.08 mm²
• maximum	4 mm²
connectable conductor cross-section stranded	
• minimum	2.5 mm²
• maximum	0.08 mm²
connectable conductor cross-section finely stranded	
• with core end processing minimum	0.14 mm²
• with core end processing maximum	2.5 mm²
• without core end processing minimum	0.08 mm²
• without core end processing maximum	2.5 mm²
type of connection	
• 1	spring-loaded terminal
• 2	spring-loaded terminal
position of the terminal	top
Mechanical Design	
height	60.93 mm
height with lowest-profile installation	36.5 mm
depth	35.25 mm
length	60.5 mm
net weight	11.6 g
material of the insulating body	Other
Environmental conditions	
ambient temperature during operation	

- minimum
- maximum

105 °C
105 °C

General Product Approval

Declaration of
Conformity

other



[Confirmation](#)



[Environmental Con-
firmations](#)

other

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WH2003-0CF07>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WH2003-0CF07>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH2003-0CF07

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



