

Product data sheet

Specifications



Illuminated push button, Harmony 9001K, metal, plastic guard flush, without cap, 30mm, spring return, 110...120V

9001K1L1

Product availability: Stock - Normally stocked in distribution facility

Price*: 158.00 USD

Main

| | |
|---------------------------------|----------------------------------|
| Range of Product | Harmony 9001K |
| Product or Component Type | Head for illuminated push-button |
| Device short name | K |
| Operator additional information | Plastic guard |

Complementary

| | |
|--------------------------------|----------------------------|
| Bezel material | Metal |
| Mounting diameter | 1.2 in (30 mm) |
| Light source | Incandescent bulb |
| Bulb base | BA 9s |
| Light block supply | Via transformer |
| Contacts type and composition | Without contact block |
| [Ie] rated operational current | 10 A, AC-15 10 A, DC-13 |
| device presentation | Basic element |
| Cap/operator or lens colour | Without cap |
| [Us] rated supply voltage | 110...120 V |
| Light block supply | Via integral transformer |
| Operator profile | Flush |
| Type of operator | Spring return |
| Supply frequency | 50...60 Hz |
| Size | 30 mm |

Environment

| | |
|---------------------------|--|
| Product Certifications | CSA LR 25490 class 3211 03 NEMA UL listed file E42259 CCN NKCR CE |
| NEMA degree of protection | NEMA 1/2/3/3R/4/6/12/13 |

Ordering and shipping details

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|-------------------|--------------|
| Category | US10CS121426 |
| Discount Schedule | 0CS1 |
| GTIN | 785901005605 |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------------|----------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.800 in (4.572 cm) |
| Package 1 Width | 2.100 in (5.334 cm) |
| Package 1 Length | 3.600 in (9.144 cm) |
| Package 1 Weight | 8.320 oz (235.868 g) |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

| | |
|--|---|
|  Mercury Free | |
|  Rohs Exemption Information | Yes |
| Reach Regulation | REACH Declaration |
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) |
| China Rohs Regulation | China RoHS declaration |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |