# Product data sheet Characteristics

## 9001K1L35GH13 PUSHBUTTON 600VAC 10A 30MM TYPE K



Product availability: Non-Stock - Not normally stocked in distribution facility



#### Complementary

Bezel material	Chromium plated metal
Mounting diameter	1.18 in (30 mm)
Light source	incandescent
Bulb base	BA 9s
Light block supply	Direct
[Us] rated supply voltage	2428 V AC/DC
Contacts type and composition	1 C/O
Connections - terminals	Screw clamp terminals
Operating position	Any position
[le] rated operational current	10 A, AC-15 10 A, DC-13
Contact operation	Standard
Device presentation	Complete product

#### Environment

Product certifications	UL listed file E42259 CCN NKCR CSA LR 25490 class 3211 03 NEMA CE
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

#### Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)	
Discount Schedule	CS1	
GTIN	00785901027294	
Package weight(Lbs)	0.18 kg (0.4 lb(US))	
Returnability	No	
Country of origin	MX	

### Offer Sustainability

Warranty

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

18 months