Product data sheet Characteristics

9001KP35A31 PILOT LIGHT 28V 30MM TYPE K +OPTIONS



Product availability: Stock - Normally stocked in distribution facility



Main		
Range of product	Harmony 9001K	
Product or component type	Pilot light	
Device short name	К	

Complementary

Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Lens type	Fresnel plastic	
Cap/operator or lens colour	Amber	
Light source	incandescent	
Bulb base	BA 9s	
Light block supply	Full voltage 28 V Direct 24 V	
Connections - terminals	Screw clamp terminals, 1 x 0.222 x 1.5 mm² IEC 60947-1	·
Shape of screw head	Round	
Operating position	Any position	
[Us] rated supply voltage	2428 V AC/DC	
Operating mode	Normal	
Device presentation	Complete product	

Environment

Product certifications	UL listed file E42259 CCN NKCR CE CSA LR25490 class 3211 03
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

Ordering and shipping details

21426 - 9001 K (NOT KA,KM,KX)	
CS1	
00785901032212	
0.15 kg (0.32 lb(US))	
Yes	
MX	
	CS1 00785901032212 0.15 kg (0.32 lb(US)) Yes

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------