

Push-to-test pilot light, Harmony 9001K, metal, polycarbonate, fresnel, white, 30mm, 110-120V

9001KT1W31

Discontinued on: 18 Oct 2020

#### (!) Discontinued

#### Main

Range of product	Harmony 9001K
Product or component type	Push-to-test pilot light
Device short name	K

### Complementary

Bezel material	Metal
Mounting diameter	30 mm
Lens type	Fresnel plastic
Cap/operator or lens colour	White
Bulb base	BA 9s
Light block supply	Via transformer 110 V AC 50/60 Hz Via transformer 120 V AC 50/60 Hz
Shape of screw head	Round
Light source	Incandescent bulb
Operating mode	Push-to-test
Lens type	Fresnel
[Us] rated supply voltage	110120 V
Light block supply	Via integral transformer
Contacts type and composition	1 C/O
Supply frequency	5060 Hz
Lens material	Polycarbonate
Size	30 mm

#### **Environment**

Product certifications	UL listed file E42259 CCN NKCR CSA LR25490 class 3211 03 CE
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	12.903 cm
Package 1 Width	5.08 cm
Package 1 Length	32.774 cm
Package 1 Weight	263.084 a

# **Contractual warranty**

Warranty 18 months

### **Sustainability**

Weee

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

### Well-being performance

Yes
REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope)
China RoHS declaration

collection and never end up in rubbish bins

The product must be disposed on European Union markets following specific waste