

Push-to-test pilot light, Harmony 9001K, metal, polycarbonate, domed, red, 30mm, LED red, 120V

9001KT38LRR9

! To be discontinued on: Aug 15, 2024

#### Main

Range of product	Harmony 9001K	
Product or component type	Push-to-test pilot light	
Device short name	К	

## Complementary

Bezel material	Metal
Mounting diameter	1.2 in (30 mm)
Lens type	Domed plastic
Cap/operator or lens colour	Red
Light source	Red LED
Bulb base	BA 9s
Light block supply	Direct 120 V
Shape of screw head	Round
Light source	LED
Operating mode	Push-to-test
Lens type	Domed
[Us] rated supply voltage	120 V
Light source colour	Red
Contacts type and composition	1 C/O
Lens material	Polycarbonate
Size	30 mm

### **Environment**

Product certifications	CSA LR25490 class 3211 03 UL listed file E42259 CCN NKCR CE
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

## **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.008 in (5.1 cm)

Package 1 Width	2.4 in (6.1 cm)
Package 1 Length	4.5 in (11.4 cm)
Package 1 Weight	6.4 oz (181.4 g)

### **Sustainability**

Weee

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

# Well-being performance

Mercury Free	
Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration

collection and never end up in rubbish bins

The product must be disposed on European Union markets following specific waste