

Product data sheet

Specifications

SQUARE D



CONTROL STATION + OPERATORS

9001KYK13

! Discontinued on: Jun 30, 2023

! Discontinued

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

| | |
|------------------------------|---|
| Range Of Product | Harmony 9001KY |
| Product Or Component Type | Control station |
| Device Short Name | 9001KY |
| Provided Equipment | Label plate STOP |
| Electrical Circuit Type | Motor |
| Contact Block Name | KA1 |
| Product Specific Application | For hoisting and mechanical handling applications |
| Level Or Class | Class II Division 2 Group G Class III |

Complementary

| | |
|-----------------------------------|---|
| Enclosure/Cubicle Description | Wall-mounted enclosure 1 cut-out Ø 30 mm |
| Enclosure Material | Die cast zinc alloy Gray |
| Type Of Installation | Indoor/outdoor |
| Control Station Composition | 1 push-button momentary 1 C/O |
| Mechanical Interlocking | Without mechanical interlock |
| Connector Type | Screw clamp connector |
| Connections - Terminals | Direct connection AWG 2) solid stranded Direct connection AWG 12) solid stranded Direct connection AWG 24) solid stranded |
| [Ue] Rated Operational Voltage | 300 V |
| [Ie] Rated Operational Current Ac | 10 A |

Environment

| | |
|---------------------------------------|--|
| Nema Degree Of Protection | NEMA 1 NEMA 13 NEMA 3 NEMA 4 |
| Environmental Characteristic | Resistant against immersion in water Dust and oil resistant |
| Product Certifications | UL Listed |
| Ambient Air Temperature For Operation | -13...140 °F (-25...60 °C) |
| Ambient Air Temperature For Storage | -40...158 °F (-40...70 °C) |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US10CS121426 |
| Discount Schedule | 0CS1 |
| Gtin | 785901039884 |
| Returnability | No |
| Country Of Origin | MX |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 12.70 in (32.258 cm) |
| Package 1 Width | 5.00 in (12.7 cm) |
| Package 1 Length | 32.26 in (81.935 cm) |
| Package 1 Weight | 4.00 lb(US) (1.814 kg) |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

Well-being performance

| | | |
|---|----------------------------|--|
|  | Reach Free Of Svhc | |
|  | Toxic Heavy Metal Free | |
|  | Mercury Free | |
|  | Rohs Exemption Information | Yes |
| | | |
| Reach Regulation | | REACH Declaration |
| | | |
| Eu Rohs Directive | | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| | | |
| China Rohs Regulation | | China RoHS declaration |
| | | |
| California Proposition 65 | | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |