

# Product data sheet

Specifications



## CONTROL STATION + OPERATORS

9001KYSK103

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 480.00 USD

### Main

Range Of Product	Harmony 9001KY
Product Or Component Type	Control station
Device Short Name	9001KY
Provided Equipment	Label plate STOP
Electrical Circuit Type	Motor
Contact Block Name	KA3
Product Specific Application	For hoisting and mechanical handling applications
Level Or Class	Class II Division 2 Group G Class III

### Complementary

Enclosure/Cubicle Description	Wall-mounted enclosure 1 cut-out Ø 30 mm
Enclosure Material	Stainless Steel
Type Of Installation	Indoor/outdoor
Control Station Composition	1 push-button momentary 1 NC
Mechanical Interlocking	Without mechanical interlock
Connector Type	Screw clamp connector
Connections - Terminals	Direct connection AWG 2) solid stranded Direct connection AWG 12) solid stranded Direct connection AWG 24) solid stranded
[Ue] Rated Operational Voltage	300 V
[Ie] Rated Operational Current Ac	10 A

### Environment

Nema Degree Of Protection	NEMA 13 NEMA 3 NEMA 4 NEMA 1
Environmental Characteristic	Resistant against immersion in water Dust and oil resistant
Product Certifications	UL Listed
Ambient Air Temperature For Operation	-13...140 °F (-25...60 °C)
Ambient Air Temperature For Storage	-40...158 °F (-40...70 °C)

### Ordering and shipping details

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Category	US10CS121426
Discount Schedule	0CS1
Gtin	785901704478
Returnability	No
Country Of Origin	MX

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	12.70 in (32.258 cm)
Package 1 Width	5.00 in (12.7 cm)
Package 1 Length	32.26 in (81.935 cm)
Package 1 Weight	3.00 lb(US) (1.361 kg)

## Contractual warranty

Warranty	18 months
----------	-----------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
	Mercury Free	
	Rohs Exemption Information	Yes
Reach Regulation		<a href="#">REACH Declaration</a>
Eu Rohs Directive		Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
China Rohs Regulation		<a href="#">China RoHS declaration</a>
California Proposition 65		WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>