





Timing Relay, Type JCK, plug In, off delay, adjustable time, 0.1 to 10 seconds, 10A, 240 VAC, 120 VAC/ 110 VDC

9050JCK21V20

Product availability: Stock - Normally stocked in distribution facility

Price*: 98.00 USD

Main

| Product Range | 9050JCK | |
|----------------|-----------|--|
| Product Type | Timer | |
| Timing Mode | Off-delay | |
| Timing Range | 0.110 s | |
| Supply Voltage | 120 V AC | |

Complementary

| Power Consumption | 2 VA | |
|---------------------------|----------------------|--|
| Current Rating | 10 A | |
| Switch Function | DPDT | |
| Contact Composition | 2 NO + 2 NC | |
| Contact Material | Silver nickel | |
| Maximum Switching Voltage | 240 V AC | |
| Mounting Type | Socket | |
| Number Of Pins | 11 | |
| Shape Of Pins | Tubular | |
| For Use With | 8501NR62 8501NR61 | |

Environment

| Certifications | UL Recognized CE UL Listed |
|--|----------------------------|
| Ambient Temperature Range - Operational | -18150 °F (-2866 °C) |
| Height | 2.40 in (61 mm) |
| Width | 1.69 in (43 mm) |
| Depth | 4.09 in (104 mm) |

Ordering and shipping details

Category US10CP221651

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Discount Schedule | 0CP2 |
|-------------------|--------------|
| Gtin | 785901032618 |
| Returnability | Yes |
| Country Of Origin | US |

Packing Units

| Unit Type Of Package 1 | PCE | |
|-----------------------------------|------------------------|--|
| Number Of Units In Package 1 | 1 | |
| Package 1 Height | 2.60 in (6.604 cm) | |
| Package 1 Width 2.00 in (5.08 cm) | | |
| Package 1 Length | 4.30 in (10.922 cm) | |
| Package 1 Weight | 5.28 oz (149.686 g) | |
| Unit Type Of Package 2 | CAR | |
| Number Of Units In Package 2 | 20 | |
| Package 2 Height | 4.50 in (11.43 cm) | |
| Package 2 Width | 10.00 in (25.4 cm) | |
| Package 2 Length | 11.00 in (27.94 cm) | |
| Package 2 Weight | 5.50 lb(US) (2.495 kg) | |

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

| Ø | Reach Free Of Svhc | |
|----------|----------------------------|-----|
| Ø | Toxic Heavy Metal Free | |
| ⊘ | Mercury Free | |
| ⊘ | Rohs Exemption Information | Yes |

Certifications & Standards

| Reach Regulation | REACh Declaration |
|--------------------------|--|
| Eu Rohs Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End of Life Information |