Product data sheet

Specifications



Plug In Timer, off delay, 0.1 to 10 minutes, 12 VAC/DC

9050JCK26V36

() Discontinued on: Jan 23, 2021

Main

product range	9050JCK
product type	Timer
timing mode	Off-delay
timing range	0.110 min
supply voltage	12 V AC/DC

Complementary

power consumption	2 VA	
current rating	10 A	
switch function	DPDT	
contact composition	2 NO + 2 NC	
contact material	Silver nickel	
maximum switching voltage	240 V AC	
mounting type	Socket	
number of pins	11	
shape of pins	Tubular	
for use with	8501NR62 8501NR61	

Environment

certifications	UL Listed UL Recognized CE
ambient temperature range - operational	-2866 °C (-18150 °F)
Height	2.4 in (61 mm)
Width	1.7 in (43 mm)
Depth	4.09 in (104 mm)

Ordering and shipping details

Category	21651-9050 JCK(NOT JCK60, 70) G P TIMERS	
Discount Schedule	CP2	
GTIN	00785901056577	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Returnability	No
Country of origin	US

Contractual warranty

Warranty

18 months

Sep 30, 2024

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

Certifications & Standards

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information