



Timing Relay, Type JCK, plug In, one shot, adjustable time, 1.2 to 120 seconds, 10A, 240 VAC, 120 VAC/110 VDC

9050JCK44V20

(!) Discontinued on: Jun 30, 2023



Main

product range	9050JCK	
product type	Timer	
timing mode	One shot	
timing range	1.2120 s	
supply voltage	120 V AC 110 V DC	

Complementary

•	
power consumption	2 VA
current rating	10 A
switch function	DPDT
contact composition	2 NO + 2 NC
contact material	Silver nickel
maximum switching voltage	240 V AC
mounting type	Socket
number of pins	11
shape of pins	Tubular
for use with	8501NR62 8501NR61

Environment

certifications	UL listed UL recognized CE	
ambient temperature range - operational	-27.865.6 °C (-18150 °F)	
Height	2.4 in (61 mm)	
Width	1.7 in (43 mm)	
Depth	4.09 in (104 mm)	

Packing Units

Jul 22, 2024

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Package 1 Height	4.300 in (10.922 cm)	
Package 1 Width	2.0000000000 in (5.08 cm)	
Package 1 Length 2.50 in (6.35 cm)		
Package 1 Weight	5.280 oz (149.685 g)	

Contractual warranty

Warranty 18 months



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Reach Free Of Svhc	
Ø	Toxic Heavy Metal Free	
⊘	Mercury Free	
⊘	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information