# Product data sheet

Specifications



# Plug In Timer, one shot, 1.8 to 180 seconds, 120 VAC 110 VDC

9050JCK45V20

() Discontinued on: Jan 23, 2021

#### Main

product range	9050JCK	
product type	Timer	
timing mode	One shot	
timing range	1.8180 s	
supply voltage	120 V AC 110 V DC	

#### Complementary

power consumption	2 VA	
current rating	10 A	
switch function	DPDT	
contact composition	2 NO + 2 NC	
contact material	Silver nickel	
maximum switching voltage	240 V AC	
mounting type	Socket	
number of pins	11	
shape of pins	Tubular	
for use with	8501NR62 8501NR61	

#### Environment

certifications	CE UL Listed UL Recognized
ambient temperature range - operational	-27.865.6 °C (-18150 °F)
Height	2.4 in (61 mm)
Width	1.7 in (43 mm)
Depth	4.09 in (104 mm)

# Ordering and shipping details

Category	21651-9050 JCK(NOT JCK60, 70) G P TIMERS	
Discount Schedule	CP2	
GTIN	00785901808701	

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Returnability	No
Country of origin	US

## **Contractual warranty**

Warranty

18 months

# Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

## Well-being performance

Reach Free Of Svhc
Toxic Heavy Metal Free
Mercury Free
Rohs Exemption Information Yes

#### **Certifications & Standards**

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information