





Plug In Timer, repeat cycle, 1.2 to 120 minutes, 24 VAC/DC

9050JCK59V14

! Discontinued on: Jan 23, 2021

Product availability: Non-Stock - Not normally stocked in distribution facility

① Discontinued

Main

product range	9050JCK
product type	Timer
timing mode	Repeat cycle
timing range	1.2120 min
supply voltage	24 V AC/DC

Complementary

· · · / · · · · · · · · · · · · · · · · · · ·		
power consumption	2 VA	
current rating	10 A	
switch function	DPDT	
contact composition	2 NO + 2 NC	
contact material	Silver nickel	
maximum switching voltage	240 V AC	
mounting type	Socket	
number of pins	8	
shape of pins	Tubular	
for use with	8501NR52 8501NR51	

Environment

certifications	UL Recognized CE UL Listed
ambient temperature range - operational	-27.865.6 °C (-18150 °F)
Height	2.4 in (61 mm)
Width	1.7 in (43 mm)
Depth	4.09 in (104 mm)

Ordering and shipping details

Category	US10CP221651
Discount Schedule	0CP2
GTIN	00785901837701

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Returnability	No	
Country of origin	US	

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Reach Free Of Svhc	
	Toxic Heavy Metal Free	
②	Mercury Free	
	Rohs Exemption Information	Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information