

Specifications

Eaton 091971

Eaton Moeller® series T5B Step switches, T5B, 63 A, flush mounting, 5 contact unit(s), Contacts: 9, 30 °, maintained, With 0 (Off) position, 0-9, Design number 15247

General specifications

PRODUCT NAME	Eaton Moeller® series T5B Step switch
CATALOG NUMBER	091971
EAN	4015080919711
PRODUCT LENGTH/DEPTH	157 mm
PRODUCT HEIGHT	88 mm
PRODUCT WIDTH	88 mm
PRODUCT WEIGHT	0.86 kg
CERTIFICATIONS	UL Category Control No.: NLRV CSA File No.: 012528 UL File No.: E36332 CSA IEC/EN 60204 UL UL 60947-4-1 CSA-C22.2 No. 60947-4-1-14 IEC/EN 60947 VDE 0660 CSA-C22.2 No. 94 CE CSA Class No.: 3211-07 IEC/EN 60947-3
CATALOG NOTES	Rated Short-time Withstand Current (Icw) for a time of 1 second
MODEL CODE	T5B-5-15247/E

Features & Functions

FITTED WITH:	Black thumb grip and front plate 0 (off) position
INSCRIPTION	0-9
NUMBER OF POLES	Single-pole

General

DEGREE OF PROTECTION	IP65 NEMA 12 NEMA 1
DEGREE OF PROTECTION (FRONT SIDE)	IP65 NEMA 12
LIFESPAN, MECHANICAL	500,000 Operations
MOUNTING METHOD	Flush mounting
MOUNTING POSITION	As required
NUMBER OF CONTACT UNITS	5
OPERATING FREQUENCY	1200 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Control switches
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SAFE ISOLATION	440 V AC, Between the contacts, According to EN 61140
SAFETY PARAMETER (EN ISO 13849-1)	B10d values as per EN ISO 13849-1, table C.1
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms
SUITABLE FOR	Branch circuits, suitable as motor disconnect, (UL/CSA) Front mounting
SWITCHING ANGLE	30 °
TYPE	Step switch

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE - MAX	50 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
CLIMATIC PROOFING	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Terminal capacities

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	1 x (1 - 25) mm ² , ferrules to DIN 46228 2 x (1.5 - 10) mm ² , ferrule to DIN 46228
TERMINAL CAPACITY (SOLID/FLEXIBLE WITH FERRULE AWG)	12 - 4
TERMINAL CAPACITY (SOLID/STRANDED)	2 x (2.5 - 16) mm ² 1 x (2.5 - 35) mm ²
SCREW SIZE	M6, Terminal screw
TIGHTENING TORQUE	4 Nm, Screw terminals 35.4 lb-in, Screw terminals

Electrical rating

RATED BREAKING

CAPACITY AT 220/230 V 520 A
(COS PHI TO IEC 60947-3)

RATED BREAKING

CAPACITY AT 400/415 V 600 A
(COS PHI TO IEC 60947-3)

RATED BREAKING

CAPACITY AT 500 V (COS PHI TO IEC 60947-3) 480 A

RATED BREAKING

CAPACITY AT 660/690 V 340 A
(COS PHI TO IEC 60947-3)

RATED OPERATING

VOLTAGE (UE) AT AC - MAX 690 V

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 220 V, 230 V, 240 V 51 A

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 380 V, 400 V, 415 V 41 A

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 500 V 33 A

RATED OPERATIONAL

CURRENT (IE) AT AC-3, 660 V, 690 V 17 A

RATED OPERATIONAL

CURRENT (IE) AT AC-21, 440 V 63 A

RATED OPERATIONAL

CURRENT (IE) AT AC-23A, 230 V 63 A

RATED OPERATIONAL

CURRENT (IE) AT AC-23A, 400 V, 415 V 63 A

RATED OPERATIONAL

CURRENT (IE) AT AC-23A, 500 V 33 A

RATED OPERATIONAL

CURRENT (IE) AT AC-23A, 690 V 23.8 A

RATED OPERATIONAL

CURRENT (IE) AT DC-1, LOAD-BREAK SWITCHES L/R = 1 MS 63 A

RATED OPERATIONAL

CURRENT (IE) AT DC-13, CONTROL SWITCHES L/R 25 A

Short-circuit rating

RATED CONDITIONAL

SHORT-CIRCUIT CURRENT (IQ) 2 kA

RATED SHORT-TIME

WITHSTAND CURRENT (ICW) 1,3 kA, Contacts, 1 second

SHORT-CIRCUIT CURRENT RATING (HIGH FAULT)

10 kA, SCCR (UL/CSA)
100 A, Class J, max. Fuse,
SCCR (UL/CSA)

SHORT-CIRCUIT PROTECTION RATING

80 A gG/gL, Fuse, Contacts

= 50 MS

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 50 A
24 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 50 A
48 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 50 A
60 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 25 A
120 V

RATED OPERATIONAL

CURRENT (IE) AT DC-23A, 20 A
240 V

RATED OPERATIONAL

CURRENT (IE) STAR-DELTA AT AC-3, 230 V
63 A

RATED OPERATIONAL

CURRENT (IE) STAR-DELTA AT AC-3, 400 V
63 A

RATED OPERATIONAL

CURRENT (IE) STAR-DELTA AT AC-3, 500 V
57.2 A

RATED OPERATIONAL

CURRENT (IE) STAR-DELTA AT AC-3, 690 V
29.4 A

RATED OPERATIONAL

POWER AT AC-3, 415 V, 50 HZ
22 kW

RATED OPERATIONAL

POWER AT AC-3, 690 V, 50 HZ
15 kW

RATED OPERATIONAL

POWER AT AC-23A, 220/230 V, 50 HZ
18.5 kW

RATED OPERATIONAL

POWER AT AC-23A, 400 V, 50 HZ
30 kW

RATED OPERATIONAL

POWER AT AC-23A, 500 V, 50 HZ
22 kW

RATED OPERATIONAL

POWER AT AC-23A, 690 V, 50 HZ
22 kW

RATED OPERATIONAL

POWER STAR-DELTA AT 220/230 V, 50 HZ
18.5 kW

RATED OPERATIONAL

30 kW

**POWER STAR-DELTA AT
380/400 V, 50 Hz**

RATED OPERATIONAL

**POWER STAR-DELTA AT
500 V, 50 Hz**

37 kW

RATED OPERATIONAL

**POWER STAR-DELTA AT
690 V, 50 Hz**

22 kW

**RATED UNINTERRUPTED
CURRENT (IU)**

63 A

**UNINTERRUPTED
CURRENT**

Rated uninterrupted
current I_u is specified for
max. cross-section.

Switching capacity

$1.6 \times I_e$ (with intermittent
operation class 12, 40 %
duty factor)

$2 \times I_e$ (with intermittent
operation class 12, 25 %
duty factor)

$1.3 \times I_e$ (with intermittent
operation class 12, 60 %
duty factor)

**NUMBER OF CONTACTS
IN SERIES AT DC-23A, 24 V**

1

**NUMBER OF CONTACTS
IN SERIES AT DC-23A, 48 V**

2

**NUMBER OF CONTACTS
IN SERIES AT DC-23A, 60 V**

3

**NUMBER OF CONTACTS
IN SERIES AT DC-23A, 120
V**

3

**NUMBER OF CONTACTS
IN SERIES AT DC-23A, 240
V**

6

**SWITCHING CAPACITY
(MAIN CONTACTS,
GENERAL USE)**

63 A, Rated uninterrupted
current max. (UL/CSA)

RATED MAKING

**CAPACITY UP TO 690 V
(COS PHI TO IEC/EN
60947-3)**

800 A

**VOLTAGE PER CONTACT
PAIR IN SERIES**

24 V

Motor rating

ASSIGNED MOTOR

**POWER AT 115/120 V, 60
HZ, 1-PHASE**

3 HP

ASSIGNED MOTOR

**POWER AT 200/208 V, 60
HZ, 1-PHASE**

7.5 HP

ASSIGNED MOTOR

**POWER AT 200/208 V, 60
HZ, 3-PHASE**

15 HP

ASSIGNED MOTOR

**POWER AT 230/240 V, 60
HZ, 1-PHASE**

10 HP

ASSIGNED MOTOR

**POWER AT 230/240 V, 60
HZ, 3-PHASE**

15 HP

ASSIGNED MOTOR

**POWER AT 460/480 V, 60
HZ, 3-PHASE**

40 HP

ASSIGNED MOTOR

**POWER AT 575/600 V, 60
HZ, 3-PHASE**

40 HP

Contacts

CONTROL CIRCUIT RELIABILITY	1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)
NUMBER OF CONTACTS	9

Actuator

ACTUATOR FUNCTION	Maintained With 0 (Off) position
ACTUATOR TYPE	Toggle
NUMBER OF SWITCH POSITIONS	10

Design verification

EQUIPMENT HEAT

DISSIPATION, CURRENT- 0 W

DEPENDENT PVID

HEAT DISSIPATION 0 W
CAPACITY PDISS

HEAT DISSIPATION PER
POLE, CURRENT- 4.5 W
DEPENDENT PVID

RATED OPERATIONAL
CURRENT FOR SPECIFIED 63 A
HEAT DISSIPATION (IN)

STATIC HEAT
DISSIPATION, NON- 0 W
CURRENT-DEPENDENT
PVS

**10.2.2 CORROSION
RESISTANCE** Meets the product
standard's requirements.

**10.2.3.1 VERIFICATION OF
THERMAL STABILITY OF
ENCLOSURES** Meets the product
standard's requirements.

**10.2.3.2 VERIFICATION OF
RESISTANCE OF
INSULATING MATERIALS
TO NORMAL HEAT** Meets the product
standard's requirements.

**10.2.3.3 RESIST. OF
INSUL. MAT. TO
ABNORMAL HEAT/FIRE
BY INTERNAL ELECT.
EFFECTS** Meets the product
standard's requirements.

**10.2.4 RESISTANCE TO
ULTRA-VIOLET (UV)
RADIATION** UV resistance only in
connection with protective
shield.

10.2.5 LIFTING Does not apply, since the
entire switchgear needs to
be evaluated.

**10.2.6 MECHANICAL
IMPACT** Does not apply, since the
entire switchgear needs to
be evaluated.

10.2.7 INSCRIPTIONS Meets the product
standard's requirements.

**10.3 DEGREE OF
PROTECTION OF
ASSEMBLIES** Does not apply, since the
entire switchgear needs to
be evaluated.

**10.4 CLEARANCES AND
CREEPAGE DISTANCES** Meets the product
standard's requirements.

**10.5 PROTECTION
AGAINST ELECTRIC
SHOCK** Does not apply, since the
entire switchgear needs to
be evaluated.

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

BROCHURES	Brochure - T Rotary Cam switch and P Switch-disconnector
CATALOGUES	P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN
DECLARATIONS OF CONFORMITY	DA-DC-00004925.pdf DA-DC-00004897.pdf
DRAWINGS	eaton-rotary-switches-mounting-t5b-non-standard-switch-dimensions-005.eps

eaton-rotary-switches-front-plate-t0-step-switch-symbol-005.eps	
eaton-general-rotary-switch-t0-step-switch-symbol-002.eps	
ECAD MODEL	DA-CE-ETN.T5B-5-15247_E
INSTALLATION INSTRUCTIONS	IL03801009Z
INSTALLATION VIDEOS	Eaton's P Switch-disconnectors used in a factory
MCAD MODEL	DA-CD-t5(b)_5_e DA-CS-t5(b)_5_e
PRODUCT NOTIFICATIONS	MZ008005ZU_Orderform_Customized_Switch.pdf MZ008006ZU_Orderform_Customized_Switch.pdf
WIRING DIAGRAMS	eaton-rotary-switches-t0-step-switch-wiring-diagram-032.eps eaton-rotary-switches-t0-step-switch-wiring-diagram-031.eps

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

