

Specifications

Photo is representative

Eaton 093047

Eaton Moeller® series T5B
Changeoverswitches, T5B, 63 A, flush
mounting, 2 contact unit(s), Contacts: 4, 90 °,
maintained, Without 0 (Off) position, 1-2,
Design number 8221

General specifications

PRODUCT NAME	Eaton Moeller® series T5B Changeover switch
CATALOG NUMBER	093047
EAN	4015080930471
PRODUCT LENGTH/DEPTH	108 mm
PRODUCT HEIGHT	88 mm
PRODUCT WIDTH	88 mm
PRODUCT WEIGHT	0.457 kg
CERTIFICATIONS	CE CSA File No.: 012528 IEC/EN 60947-3 CSA Class No.: 3211-05 UL File No.: E36332 IEC/EN 60947 UL Category Control No.: NLRV CSA-C22.2 No. 60947-4-1- 14 UL 60947-4-1 IEC/EN 60204 UL CSA-C22.2 No. 94 VDE 0660 CSA
CATALOG NOTES	Rated Short-time Withstand Current (Icw) for a time of 1 second
MODEL CODE	T5B-2-8221/E

Features & Functions

ENCLOSURE MATERIAL	Plastic
FITTED WITH:	Black thumb grip and front plate
INSCRIPTION	1-2
NUMBER OF POLES	2

General

DEGREE OF PROTECTION	IP65 NEMA 12 NEMA 1
DEGREE OF PROTECTION (FRONT SIDE)	IP65 NEMA 12
LIFESPAN, MECHANICAL	500,000 Operations
MODEL	Reverser
MOUNTING METHOD	Flush mounting
MOUNTING POSITION	As required
NUMBER OF CONTACT UNITS	2
OPERATING FREQUENCY	1200 Operations/h
OVERVOLTAGE CATEGORY	III
POLLUTION DEGREE	3
PRODUCT CATEGORY	Control switches
RATED IMPULSE WITHSTAND VOLTAGE (UIMP)	6000 V AC
SAFE ISOLATION	440 V AC, Between the contacts, According to EN 61140
SAFETY PARAMETER (EN ISO 13849-1)	B10d values as per EN ISO 13849-1, table C.1
SHOCK RESISTANCE	15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms
SUITABLE FOR	Branch circuits, suitable as motor disconnect, (UL/CSA) Front mounting
SWITCHING ANGLE	90 °
TYPE	Changeover switch

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

AMBIENT OPERATING TEMPERATURE - MAX	50 °C
--	-------

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MIN	-25 °C
---	--------

AMBIENT OPERATING TEMPERATURE (ENCLOSED) - MAX	40 °C
---	-------

CLIMATIC PROOFING	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
--------------------------	--

Terminal capacities

TERMINAL CAPACITY (FLEXIBLE WITH FERRULE)	2 x (1.5 - 10) mm ² , ferrule to DIN 46228 1 x (1 - 25) mm ² , ferrules to DIN 46228
--	---

TERMINAL CAPACITY (SOLID/FLEXIBLE WITH FERRULE AWG)	12 - 4
--	--------

TERMINAL CAPACITY (SOLID/STRANDED)	1 x (2.5 - 35) mm ² 2 x (2.5 - 16) mm ²
---	--

SCREW SIZE	M6, Terminal screw
-------------------	--------------------

TIGHTENING TORQUE	4 Nm, Screw terminals 35.4 lb-in, Screw terminals
--------------------------	--

Electrical rating

**RATED BREAKING
CAPACITY AT 220/230 V
(COS PHI TO IEC 60947-3)** 520 A

**RATED BREAKING
CAPACITY AT 400/415 V
(COS PHI TO IEC 60947-3)** 600 A

**RATED BREAKING
CAPACITY AT 500 V (COS
PHI TO IEC 60947-3)** 480 A

**RATED BREAKING
CAPACITY AT 660/690 V
(COS PHI TO IEC 60947-3)** 340 A

**RATED OPERATIONAL
CURRENT (IE)** 29.4 A at AC-3, 690 V star-
delta
63 A at AC-3, 230 V star-
delta
57.2 A at AC-3, 500 V star-
delta
63 A at AC-3, 400 V star-
delta

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
220 V, 230 V, 240 V** 51 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
380 V, 400 V, 415 V** 41 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
500 V** 33 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-3,
660 V, 690 V** 17 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-21,
440 V** 63 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-23A,
230 V** 63 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-23A,
400 V, 415 V** 63 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-23A,
500 V** 33 A

**RATED OPERATIONAL
CURRENT (IE) AT AC-23A,
690 V** 23.8 A

**RATED OPERATIONAL
CURRENT (IE) AT DC-1,** 63 A

Short-circuit rating

**RATED CONDITIONAL
SHORT-CIRCUIT CURRENT
(IQ)** 2 kA

**RATED SHORT-TIME
WITHSTAND CURRENT
(ICW)** 1,3 kA, Contacts, 1 second

**SHORT-CIRCUIT CURRENT
RATING (HIGH FAULT)** 10 kA, SCCR (UL/CSA)
100 A, Class J, max. Fuse,
SCCR (UL/CSA)

**SHORT-CIRCUIT
PROTECTION RATING** 80 A gG/gL, Fuse, Contacts

LOAD-BREAK SWITCHES**L/R = 1 MS**

RATED OPERATIONAL CURRENT (IE) AT DC-13, CONTROL SWITCHES L/R = 50 MS	25 A
--	------

RATED OPERATIONAL CURRENT (IE) AT DC-23A, 24 V	50 A
---	------

RATED OPERATIONAL CURRENT (IE) AT DC-23A, 48 V	50 A
---	------

RATED OPERATIONAL CURRENT (IE) AT DC-23A, 60 V	50 A
---	------

RATED OPERATIONAL CURRENT (IE) AT DC-23A, 120 V	25 A
--	------

RATED OPERATIONAL CURRENT (IE) AT DC-23A, 240 V	20 A
--	------

RATED OPERATIONAL POWER AT AC-3, 380/400 V, 50 HZ	22 kW
--	-------

RATED OPERATIONAL POWER AT AC-3, 415 V, 50 HZ	22 kW
--	-------

RATED OPERATIONAL POWER AT AC-3, 690 V, 50 HZ	15 kW
--	-------

RATED OPERATIONAL POWER AT AC-23A, 220/230 V, 50 HZ	18.5 kW
--	---------

RATED OPERATIONAL POWER AT AC-23A, 400 V, 50 HZ	30 kW
--	-------

RATED OPERATIONAL POWER AT AC-23A, 500 V, 50 HZ	22 kW
--	-------

RATED OPERATIONAL POWER AT AC-23A, 690 V, 50 HZ	22 kW
--	-------

RATED OPERATIONAL POWER STAR-DELTA AT 220/230 V, 50 HZ	18.5 kW
---	---------

RATED OPERATIONAL POWER STAR-DELTA AT 380/400 V, 50 HZ	30 kW
---	-------

RATED OPERATIONAL POWER STAR-DELTA AT	37 kW
--	-------

500 V, 50 HZ	
RATED OPERATIONAL POWER STAR-DELTA AT 690 V, 50 HZ	22 kW
RATED OPERATIONAL VOLTAGE (UE) AT AC - MAX	690 V
RATED UNINTERRUPTED CURRENT (IU)	63 A
UNINTERRUPTED CURRENT	Rated uninterrupted current I _u is specified for max. cross-section.

Switching capacity

LOAD RATING	1.6 x I _e (with intermittent operation class 12, 40 % duty factor)
	1.3 x I _e (with intermittent operation class 12, 60 % duty factor)
	2 x I _e (with intermittent operation class 12, 25 % duty factor)
NUMBER OF CONTACTS IN SERIES AT DC-23A, 24 V	1
NUMBER OF CONTACTS IN SERIES AT DC-23A, 48 V	2
NUMBER OF CONTACTS IN SERIES AT DC-23A, 60 V	3
NUMBER OF CONTACTS IN SERIES AT DC-23A, 120 V	3
NUMBER OF CONTACTS IN SERIES AT DC-23A, 240 V	6
SWITCHING CAPACITY (MAIN CONTACTS, GENERAL USE)	63 A, Rated uninterrupted current max. (UL/CSA)
RATED MAKING CAPACITY UP TO 690 V (COS PHI TO IEC/EN 60947-3)	800 A
VOLTAGE PER CONTACT PAIR IN SERIES	60 V

Motor rating

ASSIGNED MOTOR POWER AT 115/120 V, 60 HZ, 1-PHASE 3 HP

ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 1-PHASE 7.5 HP

ASSIGNED MOTOR POWER AT 200/208 V, 60 HZ, 3-PHASE 15 HP

ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 1-PHASE 10 HP

ASSIGNED MOTOR POWER AT 230/240 V, 60 HZ, 3-PHASE 15 HP

ASSIGNED MOTOR POWER AT 460/480 V, 60 HZ, 3-PHASE 40 HP

ASSIGNED MOTOR POWER AT 575/600 V, 60 HZ, 3-PHASE 40 HP

Contacts

CONTROL CIRCUIT RELIABILITY	1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA)
--	--

NUMBER OF AUXILIARY CONTACTS (CHANGE- OVER CONTACTS)	0
---	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY CLOSED CONTACTS)	0
--	---

NUMBER OF AUXILIARY CONTACTS (NORMALLY OPEN CONTACTS)	0
--	---

NUMBER OF CONTACTS	4
---------------------------	---

Actuator

ACTUATOR FUNCTION	Without 0 (Off) position Maintained
--------------------------	--

ACTUATOR TYPE	Short thumb-grip
----------------------	------------------

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
---	-----

HEAT DISSIPATION CAPACITY PDISS	0 W
--	-----

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	4.5 W
--	-------

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	63 A
--	------

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
---	-----

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
------------------------------------	--

10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
---	--

10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
---	--

10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
---	--

10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	UV resistance only in connection with protective shield.
---	--

10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
-----------------------	--

10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
---------------------------------	--

10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
----------------------------	--

10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
--	--

10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
---	--

10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
---	--

10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

BROCHURES

[Brochure - T Rotary Cam switch and P Switch-disconnector](#)

CATALOGUES

[P Switch-disconnectors and T Rotary cam switches catalogue CA042001EN](#)

DECLARATIONS OF CONFORMITY

[DA-DC-00004897.pdf](#) [DA-DC-00004925.pdf](#)

DRAWINGS

[eaton-rotary-switches-mounting-t5b-non-standard-switch-dimensions-002.eps](#)

	eaton-rotary-switches-front-plate-t0-changeover-switch-symbol-014.eps eaton-general-rotary-switch-t0-step-switch-symbol-002.eps eaton-rotary-switches-mounting-t0-changeover-switch-3d-drawing-002.eps
ECAD MODEL	ETN.093047.edz
INSTALLATION INSTRUCTIONS	IL03801009Z
INSTALLATION VIDEOS	Eaton's P Switch-disconnectors used in a factory
MCAD MODEL	DA-CS-t5(b)_2_e DA-CD-t5(b)_2_e
PRODUCT NOTIFICATIONS	MZ008005ZU_Orderform_Customized_Switch.pdf MZ008006ZU_Orderform_Customized_Switch.pdf
WIRING DIAGRAMS	eaton-rotary-switches-contact-t0-changeover-switch-wiring-diagram-004.eps

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

