

# Product datasheet

Specifications



Operating mechanism, flange mounted, variable depth, handle mechanism, 4in handle, NEMA 1, 3R, 4, 12 enclosure

9422A3

## Main

Product	Handle Mechanism
For Use With	All circuit breaker mechanisms Disconnect switches (30...200 A)

## Complementary

Product Type	Variable depth
Product destination	all circuit breaker mechanisms disconnect switches (30...200 A)
Enclosure Types	NEMA 1/3/3R/4/12 enclosures
Handle Length	101.6 mm

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.572 cm
Package 1 Width	9.652 cm
Package 1 Length	24.13 cm
Package 1 Weight	1.207 kg

## Contractual warranty

Warranty	18 months
----------	-----------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

## Sustainability

**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

## Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes
✓	Pvc Free	
Eu Rohs Directive		Compliant <a href="#">EU RoHS Declaration</a>
China Rohs Regulation		<a href="#">China RoHS declaration</a> Pro-active China RoHS declaration (out of China RoHS legal scope)