



Operating mechanism, flange mounted, variable depth, 30A, 600V, H, K, J, R fuseholder, switch mechanism

9422TDF60

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 537.20 USD

Main

| Range | 9422T |
|-----------------|---------------------------|
| Product | Disconnect Switch |
| Disconnect Type | Fusible disconnect switch |

Complementary

| Mounting Type | Flange rod variable depth |
|-------------------|---------------------------|
| Current Rating | 60 A |
| Horsepower Rating | 15 hp 200 V AC |
| | 15 hp 230 V AC |
| | 30 hp 460 V AC |
| | 50 hp 575 V AC |
| | 10 hp 250 V DC |
| Fuse Rating | 60 A 250 V |
| | 30 A 600 V |
| Handle Type | Ordered separately |
| Fuse Type | R |
| | K |
| | Н |
| | J |

Environment

| Certifications | CSA |
|----------------|---------------|
| | UL Recognized |

Ordering and shipping details

| Category | US10CP121732 |
|-------------------|--------------|
| Discount Schedule | 0CP1 |
| Gtin | 785901879794 |
| Returnability | No |
| Country Of Origin | MX |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|-----|
| Number Of Units In Package 1 | 1 |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Package 1 Height | 7.13 in (18.100 cm) |
|------------------------------|---------------------------|
| Package 1 Width | 11.10 in (28.200 cm) |
| Package 1 Length | 15.91 in (40.400 cm) |
| Package 1 Weight | 6.18 lb(US) (2.805 kg) |
| Unit Type Of Package 2 | P12 |
| Number Of Units In Package 2 | 12 |
| Package 2 Height | 35.433 in (90.000 cm) |
| Package 2 Width | 31.496 in (80.000 cm) |
| Package 2 Length | 47.244 in (120.000 cm) |
| Package 2 Weight | 100.66 lb(US) (45.660 kg) |

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

| Reach Free Of Svhc | |
|----------------------------|---|
| Toxic Heavy Metal Free | |
| Mercury Free | |
| Rohs Exemption Information | Yes |
| | |
| Reach Regulation | REACh Declaration |
| Eu Rohs Directive | Compliant |
| | EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope) |
| California Proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |