

PRODUCT-DETAILS

9C54U2 50A,CON,3P4W,DG,U2,3P250V



General Information	
Extended Product Type	9C54U2
Product ID	7TAA057190R0003
EAN	5415022516746
Catalog Description	50A,CON,3P4W,DG,U2,3P250V
Long Description	DuraGard Female Connector, 50 Amp, 3 Pole 4 Wire, 3 Phase 250 Volts

EAN	5415022516746
UPC	708917205432
Country of Origin	Mexico (MX)
Selling Unit of Measure	each

Container Information	
Package Level 1 Units	1 EA
Package Level 1 Width	63.5 mm

© 2025 ABB. All rights reserved.

Subject to change without notice

	2.5 in
Package Level 1 Height	63.5 mm
	2.5 in
Package Level 1 Depth /	190.5 mm
Length	7.5 in
Package Level 2 Units	50 EA
Package Level 2 Width	336.55 mm
-	13.25 in
Package Level 2 Height	419.1 mm
	16.5 in
Package Level 2 Depth /	336.55 mm
Length	13.25 in

Additional Information	
Application	For use where electrical connections need protection from water and/or dust entrance to the contacts or the wiring compartment.
Brand / Label	Russellstoll
Effective Date	19960411
Material	DuraV
Product Name	ELECTRICAL APPARATUS FOR SWITCHING OR PROTECTING ELECTRICAL CIRCUITS, OR FOR MAKING CONNECTION TO/ IN ELECTRICAL CIRCUIT
Product Type	DuraGard Waterproof Connections
Special Functions	Not just "watertight", Waterproof for washdown duty (DurORing Sealing) that eliminates the need for costly "weather boots" or "adapters."
Standards	UL e2630

Certificates and Declarations	
Data Sheet, Technical Information	9C54U2

External Classifications and Standards	
ETIM 7	EC001322 - Round socket/plug for high currents
ETIM 8	EC001322 - Round socket/plug for high currents
UNSPSC	39121406
IDEA Granular Category Code (IGCC)	4536 >> Electrical receptacles

Categories

 $\label{eq:low-voltage-products} Low \ Voltage \ Products \ and \ Systems \ \rightarrow \ Installation \ Products \ \rightarrow \ Wire \ Management \ and \ Connectivity \ \rightarrow \ Pin \ \& \ Sleeve \ Connectors$

© 2025 ABB. All rights reserved.

