

PRODUCT-DETAILS

A300-30-11-86

A300-30-11 400-415V 50Hz / 415-440V 60Hz

Contactor



General Information

Extended Product Type	A300-30-11-86
Product ID	1SFL551001R8611
EAN	7320500214183
Catalog Description	A300-30-11 400-415V 50Hz / 415-440V 60Hz Contactor
Long Description	A 3-phase Contactor suitable for various applications such as Motor starting, Isolation, Bypass and Distribution application up to max 690 V. Operated with control voltage, versions from 24....690 AC, 50 and 60 Hz

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900
Replacement Product ID (NEW)	1SFL587002R1411

Popular Downloads

Data Sheet, Technical Information	1SBC100192C0206
Instructions and Manuals	1SFC380003-89
Dimension Diagram	53540930-2

Dimensions

Product Net Width	140 mm
Product Net Depth / Length	180.5 mm
Product Net Height	227 mm
Product Net Weight	5.4 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Main Circuit 690 V
Rated Frequency (f)	Main Circuit 50/60 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors q = 40 °C 500 A
Rated Operational Current AC-1 (I_e)	(690 V) 40 °C 500 (690 V) 55 °C 400 (690 V) 70 °C 325
Rated Operational Current AC-3 (I_e)	(415 V) 55 °C 300 A (440 V) 55 °C 280 A (500 V) 55 °C 280 A (690 V) 55 °C 280 A (380 / 400 V) 55 °C 305 A (220 / 230 / 240 V) 55 °C 305
Rated Operational Power AC-3 (P_e)	(415 V) 160 kW (440 V) 160 kW (500 V) 200 kW (690 V) 250 kW (380 / 400 V) 160 kW (220 / 230 / 240 V) 90 kW
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I_e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I_e AC-3
Short-Circuit Protective Devices	gG Type Fuses 500 A
Rated Short-time Withstand Current (I_{cw})	at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 2400 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 500 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 1100 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 3500 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 1500 A
Maximum Breaking Capacity	cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 3000 A cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 2500 A
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 300 cycles per hour
Rated Operational Current DC-1 (I_e)	(110 V) 2 Poles in Series, 40 °C 450 A (220 V) 3 Poles in Series, 40 °C 450 A

Rated Operational Current DC-3 (I_e)	(110 V) 2 Poles in Series, 40 °C 450 A (220 V) 3 Poles in Series, 40 °C 450 A
Rated Operational Current DC-5 (I_e)	(110 V) 2 Poles in Series, 40 °C 450 A (220 V) 3 Poles in Series, 40 °C 450 A
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Mechanical Durability	5 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70$ °C)
Rated Control Circuit Voltage (U_c)	50 Hz 400 ... 415 V 60 Hz 415 ... 440 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 60 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 65 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 1350 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 1550 V·A
Operate Time	Between Coil De-energization and NC Contact Closing 7 ... 13 ms Between Coil De-energization and NO Contact Opening 10 ... 16 ms Between Coil Energization and NC Contact Opening 12 ... 30 ms Between Coil Energization and NO Contact Closing 17 ... 35 ms
Connecting Capacity Main Circuit	Bar 32 mm ² Rigid Al-Cable 2 x 95 ... 120 mm ² Rigid Cu-Cable 16 ... 240 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Flexible 2x0.75 ... 2.5 mm ² Solid 1 x 1 ... 4 mm ² Stranded 2 x 1 ... 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Connecting Terminals (delivered in open position) Main Poles	Flat type c/w screws and bolts
Terminal Type	Main Circuit: Bars

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
General Use Rating UL/CSA	(600 V AC) 400 A
Horsepower Rating UL/CSA	(200 V AC) Three Phase 100 hp (208 V AC) Three Phase 100 hp (220 ... 240 V AC) Three Phase 100 hp (440 ... 480 V AC) Three Phase 250 hp (550 ... 600 V AC) Three Phase 300 hp

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 U_c) -25 ... +50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 U_c) -40 ... +70 °C Close to Contactor for Storage -40 ... +70 °C
Maximum Operating Altitude Permissible	3000 m

Resistance to Shock acc.
to IEC 60068-2-27

Shock Direction: A 5 K40
Shock Direction: B1 5 K40
Shock Direction: B2 5 K40
Shock Direction: C1 5 K40
Shock Direction: C2 5 K40

RoHS Status

Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

BV Certificate	09826/C0 BV
CCC Certificate	CQC_2008010304279325
CSA Certificate	306708
Declaration of Conformity - CE	2CMT2015-005436
DNV Certificate	DNV_E-12191
Environmental Information	1SFC101003D0201
GL Certificate	GL_15529-00HH
Instructions and Manuals	1SFC380003-89
LOVAG Certificate	SE9837128
LR Certificate	LR_12-70003
RINA Certificate	ELE060313XG/001
RMRS Certificate	RMRS_12-03683-315
RoHS Information	2CMT2015-005436

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	203 mm
Package Level 1 Depth / Length	245 mm
Package Level 1 Height	188 mm
Package Level 1 Gross Weight	6.1 kg
Package Level 1 EAN	7320500214183

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4755 >> Contactors
E-Number (Norway)	4115258
E-Number (Sweden)	3227897

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

