

Product data sheet

Specifications



iEM3300 energy meter - 125 A

A9MEM3300

Product availability: Non-Stock - Not normally stocked in distribution facility

Price*: 690.46 USD

Main

Range	Acti9
Range Of Product	Acti9 iEM3000
Device Short Name	iEM3300
Product Or Component Type	Energy meter

Complementary

Poles Description	1P + N 3P + N 3P
Type Of Measurement	Active energy
Device Application	Partial meter Sub billing
Accuracy Class	Class 1 active energy IEC 62053-21 Class 1 active energy IEC 61557-12 Class B active energy EN 50470-3
Input Type	Direct input
Line Rated Current	125 A
Rated Voltage	100...277 V 173...480 V
Network Frequency	50 Hz 60 Hz
Technology Type	Electronic
Display Type	LCD display
Sampling Rate	32 samples/cycle
Measurement Current	0...125 A
Maximum Value Measured	99999999.9 kWh
Communication Port Protocol	-
Communication Port Support	-
Local Signalling	Green indicator light power ON Yellow flashing LED accuracy checking
Number Of Inputs	0
Number Of Outputs	0
Mounting Mode	Clip-on
Mounting Support	DIN rail
Connections - Terminals	screw terminals 0.08 in² (50 mm²)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Overvoltage Category	III
Standards	BS EN 61557-12:2021 IEC 61557-12:2021 EN 61557-12:2021 BS EN 61326-1 IEC 61326-1 EN 61326-1 BS EN 62052-11:2020 IEC 62052-11:2020 EN 62052-11:2020 BS EN 62053-21 IEC 62053-21 EN 62053-21 BS EN 62052-31:2015 IEC 62052-31:2015 EN 62052-31:2015 BS EN 61010-1:2010 EN 61010-1:2010 IEC 61010-1:2010 UL 61010-1:2010 BS EN 61010-2-30 IEC 61010-2-30 EN 61010-2-30 UL 61010-2-30 ANSI C12.16
Product Certifications	CE IEC 61010-1 safety) CE EN 61557-12 power monitor) CE EN/IEC 61326-1 EMC) UKCA BS EN 61010-1 safety) UKCA BS EN 61557-12 power monitor) UKCA BS EN 61326-1 EMC) CULus UL 61010-1 safety) CULus EN 61010-1 safety) EAC sub-meter) KZ NMI M 6-1 KZ NMI NMI M 6-1

Environment

Ip Degree Of Protection	IP40 front panel: conforming to IEC 60529 IP20 body: conforming to IEC 60529
Pollution Degree	2
Relative Humidity	5...95 % 122 °F (50 °C)
Ambient Air Temperature For Operation	-13...158 °F (-25...70 °C) - IEC
Ambient Air Temperature For Storage	-40...185 °F (-40...85 °C)
Operating Altitude	< 6561.68 ft (2000 m)
Color	White
9 Mm Pitches	14
Width	4.96 in (126 mm)
Height	4.06 in (103.2 mm)
Depth	2.73 in (69.3 mm)

Ordering and shipping details

Category	US10PL109786
Discount Schedule	0PL1
Gtin	3606480696381
Returnability	Yes
Country Of Origin	SG

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.35 in (8.5 cm)
Package 1 Width	4.41 in (11.2 cm)
Package 1 Length	5.16 in (13.1 cm)
Package 1 Weight	24.23 oz (687 g)
Unit Type Of Package 2	S03
Number Of Units In Package 2	18
Package 2 Height	11.81 in (30 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	27.82 lb(US) (12.619 kg)
Unit Type Of Package 3	P12
Number Of Units In Package 3	144
Package 3 Height	5.91 in (15 cm)
Package 3 Width	31.50 in (80 cm)
Package 3 Length	47.24 in (120 cm)
Package 3 Weight	246.79 lb(US) (111.944 kg)

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓

Mercury Free

✓

Rohs Exemption Information

Yes

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California Proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov