



Main

Range of product	Terminal blocks
Product or component type	Terminal block
Technology type	Screw technology
Terminal block type	Lug-lug
Fixing mode	Clip-on mounting on 35 mm notched symmetrical rail Clip-on mounting on 35 mm symmetrical DIN rail
Nominal cross section	95 mm ²
Length	92 mm
Colour	Grey
Number of points	2
Sale per indivisible quantity	10

Complementary

Width	32 mm
Height	70 mm on 35 mm notched symmetrical rail 62.5 mm on 35 mm symmetrical DIN rail
Cable cross section	<= 95 mm ² , flexible <= 95 mm ² , solid
Bolt diameter	M10
Busbar cross section	5 x 18 mm
Tightening torque	10 N.m, M12 conforming to EN 60999 10 N.m, M12 conforming to IEC 60974-1
[Ue] rated operational voltage	1000 V AC VDE group C 1200 V DC VDE group C 1000 V conforming to EN/IEC 60947-7-1 500 V AC/DC conforming to UTE category C 600 V, 0 AWG - 350 kcmil CSA 600 V, 0 AWG - 350 kcmil UL
[Ie] rated operational current	250 A VDE group C 230 A, 0 AWG - 350 kcmil CSA 230 A, 0 AWG - 350 kcmil UL 3...225 A conforming to EN/IEC 60947-7-1
Product weight	169 g

Environment

Dielectric test voltage	8 kV conforming to EN/IEC 60947-7-1
Product certifications	ASEV CSA DNV GL LR UL
RoHS EUR status	Compliant
RoHS EUR conformity date	0606

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.