
# **Product datasheet**





# connection sub-base ABE7 - for Twido extension - 16 outputs

ABE7E16SPN20

- ! Discontinued on: 24-Nov-2020
- ! End-of-service on: 30-Jun-2022

! Discontinued

## Main

Range of product	Modicon ABE7
Product or component type	Passive discrete I/O sub-base
[Us] rated supply voltage	24 V DC for controller side 24 V DC for sensor/controller side
Number of channels	16
Number of terminal per channel	2
Connections - terminals	Screw type terminals, 1 x 0.091 x 1.5 mm² (AWG 28AWG 16) flexible with cable end
	Screw type terminals, 1 x 0.141 x 2.5 mm <sup>2</sup> (AWG 26AWG 12) solid
	Screw type terminals, 1 x 0.141 x 2.5 mm² (AWG 26AWG 14) flexible without cable end
	Screw type terminals, 2 x 0.092 x 0.75 mm² (AWG 28AWG 20) flexible with cable end
	Screw type terminals, 2 x 0.22 x 2.5 mm² (AWG 28AWG 16) solid
Connector destination	Twido programmable controller

## Complementary

Joinpromontar y	
Supply voltage limits	1930 V DC (controller side) conforming to IEC 61131-2 20.428.8 V DC (sensor/controller side) conforming to IEC 61131-2
Discrete output number	16
Discrete output logic	Source
Discrete output voltage	24 V
Discrete output voltage type	DC
Product compatibility	TWDDDO32TK TWDDDO16TK
Status LED	1 LED for power ON
Polarity distribution	1 common/16 channels for output
Short-circuit protection	2 A internal fuse, 5 x 20 mm, fast blow (controller side)
Connector type	HE-10
Pin number	20 pins
Fixing mode	By clips, mounting on 35 mm symmetrical DIN rail conforming to IEC 60715 By screws
Maximum supply current	2 A
Switched current	100 mA for output circuit
Maximum current per output common	1.6 A

Life Is On Schneider 19-Jul-2024

Voltage drop on power supply fuse	0.3 V
[Ui] rated insulation voltage	2000 V terminals/mounting rails
Overvoltage category	Il conforming to IEC 60664-1
Tightening torque	0.6 N.m with flat Ø 3.5 mm screwdriver
Net weight	0.45 kg

# **Environment**

Product certifications	UL CSA
IP degree of protection	IP2X conforming to IEC 60529
Resistance to incandescent wire	750 °C conforming to IEC 60695-2-11
Shock resistance	15 gn for 11 ms conforming to IEC 60068-2-27
Vibration resistance	2 gn (f= 10150 Hz) conforming to IEC 60068-2-6
Resistance to electrostatic discharge	4 kV (contact) level 3 conforming to IEC 61000-4-2 8 kV (air) level 3 conforming to IEC 61000-4-2
Resistance to radiated fields	10 V/m (800000002000000000 Hz) conforming to IEC 61000-4-3 level 3
Resistance to fast transients	2 kV level 3 conforming to IEC 61000-4-4
Ambient air temperature for operation	-560 °C conforming to IEC 61131-2
Ambient air temperature for storage	-4080 °C conforming to IEC 61131-2
Pollution degree	2 conforming to IEC 60664-1

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.000 cm
Package 1 Width	8.200 cm
Package 1 Length	13.700 cm
Package 1 Weight	195.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	16
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	3.836 kg

# **Contractual warranty**

Warranty 18 months



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

# Well-being performance



Mercury Free



Rohs Exemption Information

Yes

## **Certifications & Standards**


Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

# **Product datasheet**

## ABE7E16SPN20

## **Dimensions Drawings**

#### **Dimensions**




(1) ABE7BV10 / BV20 / BV20TB

# ABE7E16SPN20

Mounting and Clearance

# Mounting




# **Product datasheet**


# ABE7E16SPN20

Connections and Schema

## HE10 16 Channels



## Wiring Diagram




(1) Inductive load

## ABE7E16SPN20

#### Performance Curves

# **Curves for Determining Cable Type and Length According to the Current**



- L Cable length
- I<sub>T</sub> Total current per sub base (A)
- IA Average current per channel (mA)
- (1) Cables ABFT2••••• c.s.a. 0.08 mm<sup>2</sup> (AWG 28)

The curves are given for a voltage drop of 1 V in the cable. For n volts tolerance, multiply the length determined from the graph by n.