Specification





(!) Discontinued

regulated SMPS - single phase - 100..240 V input - 24 V output - 150 W

ABL1REM24062

Discontinued on: 11 Nov 2020

! En

! End-of-service on: 25 Jan 2021

EAN Code: 3389110638332

Main

Range Of Product	Phaseo Dedicated	
Product Or Component Type	Power supply	
Power Supply Type	Regulated switch mode	
Rated Power In W	150 W	
Main Input Voltage	100120 V AC single phase 200240 V AC single phase 180370 V DC	
Output Voltage	24 V DC	
Power Supply Output Current 6.2 A		
Operating Position Any position		
Vibration Resistance	2 gn (f= 9150 Hz) conforming to EN/IEC 61131-2 3.5 mm (f= 59 Hz) conforming to EN/IEC 61131-2	
Name Of Test	Conducted interference conforming to EN 61000-4-8 level 4 Electrostatic discharges conforming to EN/IEC 61000-4-2 level 3 Induced electromagnetic field conforming to EN/IEC 61000-4-6 level 3 Radiated electromagnetic field conforming to EN/IEC 61000-4-3 level 3 Rapid transient conforming to IEC 61000-4-4 level 3 Conducted/radiated emissions conforming to EN 55022 class B Conducted/radiated emissions conforming to EN/IEC 55011 Emission conforming to EN/IEC 61000-6-3 Primary outage conforming to IEC 61000-4-11 Surge conforming to EN/IEC 61000-4-5	

Complementary

Input Voltage Limits	170264 V
	85132 V
Network Frequency	4763 Hz
Inrush Current	50 A at 115 V AC
	100 A at 230 V AC
Cos Phi	0.65
Efficiency	80 %
Power Dissipation In W	37.5 W
Current Consumption	5 A at 100 V
	2.5 A at 240 V
Input Protection Type	Integrated fuse (not interchangeable)
Output Voltage Limits	21.626.4 V

Line And Load Regulation	+/- 3 %	
Holding Time	>= 10 ms at 100 V >= 40 ms at 240 V	
Output Protection Type	Against overload, protection technology: 1.11.5 x In Against overvoltage, protection technology: tripping if U > 1.25 x Un Against short-circuits, protection technology: automatic reset Thermal	
Connections - Terminals	For ground connection: screw type terminals, connection capacity: 1 x 4 mm² AWG 12 For input connection: screw type terminals, connection capacity: 2 x 4 mm² AWG 12 For output connection: screw type terminals, connection capacity: 4 x 4 mm² AWG 12	
Marking	CE	
Mounting Support	Reversible mounting bracket Panel	
Operating Altitude	2000 m	
Output Coupling	Series Parallel	
Overvoltage Category		
Meantime Between Failure [Mtbf]] 100000 h at 40 °C	
Status Led	1 LED (green) output voltage	
Net Weight	0.73 kg	

Environment

Product Certifications	TUV 60950-1
	KC
	RCM
	cCSAus
	CSA 22-2 No 60950-1
	EAC
	UL 508
Environmental Characteristic	EMC conforming to EN 50081-1
	EMC conforming to EN 50082-2
	EMC conforming to EN 61000-6-3
	EMC conforming to EN/IEC 61000-6-2
	Safety conforming to EN/IEC 60950-1
	Safety conforming to EELV
	Salety conforming to SELV
Ip Degree Of Protection	IP20 conforming to EN/IEC 60950
Ambient Air Temperature For	045 °C (without derating)
Operation	4560 °C (with derating factor)
Ambient Air Temperature For	-2585 °C
Storage	
Relative Humidity	2090 %
Overvoltage Category	Class I conforming to VDE 0106-1
Pollution Degree	2
Dielectric Strength	1500 V between input and ground
	3000 V between input and output
	500 V between hiput and ground
	JOO V DELWEEN OULPUL AND GLOUND

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.8 cm
Package 1 Width	12 cm

Package 1 Length	23.5 cm	
Package 1 Weight	879 a	

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

	Mercury Free	
⊘	Rohs Exemption Information	Yes
⊘	Pvc Free	


Certifications & Standards

Reach Regulation	REACh Declaration	
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China Rohs Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	

ABL1REM24062

Dimensions Drawings

Dimensions



Dimensions in mm

а	L	Р
194	200	50


Dimensions in in.

а	L	Р
7.64	7.87	1.97

ABL1REM24062


Mounting and Clearance

Clearance



Mounting Way


Mounting on Vertical Plane



Mounting on Horizontal Plane



Direct Mounting by 2 M4 x 20 Screws



Dimensions in mm


а	
194	

Dimensions in in

а	
7.64	


ABL1REM24062

Mounting on the Back on ABL 1A01 Reversible Bracket by Three 4 mm Diameter Screws



Mounting on ABL 1A02 Clip-on Mounting on 35 mm Rail





ABL1REM24062

Mounting by the Back



Dimensions in mm

b	С
28	48


Dimensions in in.

b	С
1.10	1.89

ABL1REM24062


Connections and Schema

Internal Wiring Diagram




Series or Parallel Connection

Series Connection



Parallel Connection




(1) 15 A/100 V Shottky diode

ABL1REM24062


Performance Curves

Derating Curves

Mounting on Vertical Plane



Mounting on Horizontal Plane



Load Limits Curve

