

PRODUCT-DETAILS

AF1250-30-11-68

AF1250-30-11 24-60V DC Contactor



Generell informasjon

Extended Product Type	AF1250-30-11-68
Product ID	1SFL647001R6811
EAN	7320500346075
Catalog Description	AF1250-30-11 24-60V DC Contactor
Long Description	A 3-phase Contactor suitable for various applications such as, Isolation, By-pass and Distribution application up to max 1000 V. Operated with wide control voltage range 22-60 V, DC

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	1SBC100192C0206
Instructions and Manuals	1SFC380023-en

Dimensions

Product Net Width	210 mm
Product Net Depth / Length	242 mm
Product Net Height	344 mm
Product Net Weight	14.6 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Rated Operational Voltage	Main Circuit 1000 V
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $q = 40^\circ\text{C}$ 1050 A
Rated Operational Current AC-1 (I_e)	(1000 V) 40°C 1260 A (1000 V) 55°C 1040 A (1000 V) 70°C 875 A (690 V) 40°C 1260 (690 V) 55°C 1040 (690 V) 70°C 875
Rated Breaking Capacity AC-3 acc. to IEC 60947-4-1	8 x I_e AC-3
Rated Making Capacity AC-3 acc. to IEC 60947-4-1	10 x I_e AC-3
Rated Short-time Withstand Current (I_{cw})	at 40°C Ambient Temp, in Free Air, from a Cold State 10 s 7200 A at 40°C Ambient Temp, in Free Air, from a Cold State 15 min 1500 A at 40°C Ambient Temp, in Free Air, from a Cold State 1 min 4000 A at 40°C Ambient Temp, in Free Air, from a Cold State 1 s 8000 A at 40°C Ambient Temp, in Free Air, from a Cold State 30 s 5200 A
Maximum Breaking Capacity	$\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 440 V 7500 A $\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 690 V 7000 A
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour
Rated Operational Current DC-1 (I_e)	(220 V) 3 Poles in Series, 40°C 1250 A (600 V) 3 Poles in Series, 40°C 1250 A (850 V) 3 Poles in Series, 40°C 1250 A
Rated Operational Current DC-3 (I_e)	(220 V) 3 Poles in Series, 40°C 1250 A (600 V) 3 Poles in Series, 40°C 1250 A (850 V) 3 Poles in Series, 40°C 1250 A
Rated Operational Current DC-5 (I_e)	(220 V) 3 Poles in Series, 40°C 1250 A (600 V) 3 Poles in Series, 40°C 1250 A (850 V) 3 Poles in Series, 40°C 1250 A
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp})	Main Circuit 8 kV
Mechanical Durability	0.5 million
Maximum Mechanical Switching Frequency	300 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U_c Min. ... 1.1 x U_c Max. (at $\theta \leq 70^\circ\text{C}$)

Rated Control Circuit Voltage (U_c)	DC Operation 24 ... 60 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 12 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 12 V·A Holding at Max. Rated Control Circuit Voltage DC 5.5 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 780 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 780 V·A Pull-in at Max. Rated Control Circuit Voltage DC 785 V·A
Operate Time	Between Coil De-energization and NC Contact Closing 50 ... 70 ms Between Coil De-energization and NO Contact Opening 53 ... 73 ms Between Coil Energization and NC Contact Opening 45 ... 115 ms Between Coil Energization and NO Contact Closing 50 ... 120 ms
Connecting Capacity Main Circuit	Bar 50 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible 1x0.75 ... 2.5 mm ² Solid 2 x 1 ... 4 mm ² Stranded 2 x 1 4 mm ²
Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP00
Connecting Terminals (delivered in open position) Main Poles	M 3.5 (+,-) pozidriv 2 screw with cable clamp
Terminal Type	Main Circuit: Bars

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 1000 V
General Use Rating UL/CSA	(1000 V AC) 1210 A

Environmental

Ambient Air Temperature	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 Uc) -25 ... +50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 Uc) -40 ... +70 °C Close to Contactor for Storage -40 ... +70 °C
Maximum Operating Altitude Permissible	3000 m
Resistance to Shock acc. to IEC 60068-2-27	Shock Direction: A 5 K40 Shock Direction: B1 5 K40 Shock Direction: B2 5 K40 Shock Direction: C1 5 K40 Shock Direction: C2 5 K40
RoHS Status	Following EU Directive 2015/863 July 22, 2019 (RoHS 3)

Certificates and Declarations (Document Number)

ABS Certificate	15-LD1408622-PDA
BV Certificate	BV_13409-C0BV
CB Certificate	SE-82865
CCC Certificate	CQC_2006010304213519
CCS Certificate	GB14T00030
cUL Certificate	UL_20130930-E73397

Declaration of Conformity - CE	2CMT2019-005796
DNV GL Certificate	TAE00001W1
EAC Certificate	9AKK107046A8618
Environmental Information	1SFC101037D0201 1SAC200045H0007
Instructions and Manuals	1SFC380023-en
LR Certificate	16-20064
PRS Certificate	TE_2092_880423_16
RINA Certificate	ELE060313XG_002
RMRS Certificate	9AKK107045A6978
RoHS Information	2CMT2019-005796
UL Listing Card	UL_E73397

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	280 mm
Package Level 1 Depth / Length	375 mm
Package Level 1 Height	310 mm
Package Level 1 Gross Weight	16 kg
Package Level 1 EAN	7320500346075

Classifications

Object Classification Code	Q
ETIM 4	EC000066 - Magnet contactor, AC-switching
ETIM 5	EC000066 - Magnet contactor, AC-switching
ETIM 6	EC000066 - Power contactor, AC switching
ETIM 7	EC000066 - Power contactor, AC switching
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4755 >> Contactors
E-Number (Norway)	4115380
E-Number (Sweden)	4115380

Kategorier

Lavspenningsprodukter → Startapparater → Kontaktorer → Blokk-kontaktorer

