



 PRODUCT-DETAILS

AF12N0R-30-22-11

AF12N0R-30-22-11 24-60V50/60HZ 20-60VDC Reversing Contactor



General Information

| | |
|-----------------------|---|
| Extended Product Type | AF12N0R-30-22-11 |
| Product ID | 1SBX303301R1122 |
| EAN | 3471523020313 |
| Catalog Description | AF12N0R-30-22-11 24-60V50/60HZ 20-60VDC Reversing Contactor |
| Long Description | AF12N0R-30-22-11 24-60V50/60HZ 20-60VDC Reversing Contactor |

Ordering

| | |
|------------------------|---------|
| Minimum Order Quantity | 1 piece |
|------------------------|---------|

Popular Downloads

| | |
|-------------------------|-----------------|
| CAD Dimensional Drawing | 2CDC001079B0201 |
|-------------------------|-----------------|

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 90 mm |
| Product Net Depth / Length | 102.5 mm |
| Product Net Height | 104 mm |
| Product Net Weight | 0.662 kg |

Technical

| | |
|---|---|
| Number of Main Contacts NO | 3 |
| Number of Main Contacts NC | 0 |
| Number of Auxiliary Contacts NO | 2 |
| Number of Auxiliary Contacts NC | 2 |
| Number of Poles | 3P |
| Standards | IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60335-2-40 LZGH2 A2L, UL 60947-4-1, CSA C22.2 No. 60335-2-40 LZGH2 A2L, CSA C22.2 No. 60947-4-1 |
| Rated Operational Voltage | Auxiliary Circuit 690 V Main Circuit 690 V |
| Rated Frequency (f) | Auxiliary Circuit 50 / 60 Hz Control Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz |
| Rated Operational Current AC-1 (I_e) | (1000 V) 60 °C 28 A (690 V) 40 °C 28 A (690 V) 70 °C 24 A |
| Rated Operational Current AC-3 (I_e) | (415 V) 60 °C 12 A (440 V) 60 °C 12 A (500 V) 60 °C 12.5 A (690 V) 60 °C 9 A (380 / 400 V) 60 °C 12 A (220 / 230 / 240 V) 60 °C 12 A |
| Rated Operational Current AC-3e (I_e) | (415 V) 60 °C 12 A (440 V) 60 °C 12 A (500 V) 60 °C 12.5 A (690 V) 60 °C 9 A (380 / 400 V) 60 °C 12 A (220 / 230 / 240 V) 60 °C 12 A |
| Rated Operational Current AC-15 (I_e) | (500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A |
| Rated Operational Current DC-13 (I_e) | (24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W |
| Rated Operational Power AC-3 (P_e) | (415 V) 5.5 kW (440 V) 5.5 kW (500 V) 7.5 kW (690 V) 7.5 kW (380 / 400 V) 5.5 kW (220 / 230 / 240 V) 3 kW |
| Rated Operational Power AC-3e (P_e) | (415 V) 5.5 kW (440 V) 5.5 kW (500 V) 7.5 kW (690 V) 7.5 kW (380 / 400 V) 5.5 kW (220 / 230 / 240 V) 3 kW |
| Rated Short-time Withstand Current Low Voltage (I_{cw}) | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 150 A at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 35 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 60 A at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 300 A at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 80 A |

| | |
|---|--|
| | for 0.1 s 140 A for 1 s 100 A |
| Maximum Breaking Capacity | cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 440 V 250 A cos phi=0.45 (cos phi=0.35 for I _e > 100 A) at 690 V 106 A |
| Rated Insulation Voltage (U _i) | acc. to IEC 60947-4-1 690 V acc. to IEC 60947-5-1 690 V acc. to UL/CSA 600 V |
| Rated Impulse Withstand Voltage (U _{imp}) | 6 kV |
| Maximum Electrical Switching Frequency | (AC-15) 1200 cycles per hour (DC-13) 900 cycles per hour |
| Rated Control Circuit Voltage (U _c) | 50 Hz 24 ... 60 V 60 Hz 24 ... 60 V DC Operation 20 ... 60 V |
| Power Loss | at 6 A per Pole 0.1 W at Rated Operating Conditions AC-1 per Pole 1 W at Rated Operating Conditions AC-3 per Pole 0.2 W |
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting by Screws (not supplied) | 2 x M4 screws placed diagonally |
| Connecting Capacity Main Circuit | Flexible with Ferrule 1/2x 0.75 ... 6 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 4 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Rigid Solid 1/2x 1 ... 4 mm ² Rigid Stranded 1/2x 1 ... 6 mm ² |
| Connecting Capacity Auxiliary Circuit | Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ² |
| Connecting Capacity Control Circuit | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Rigid Solid 1/2x 1 ... 2.5 mm ² Rigid Stranded 1/2x 1 ... 2.5 mm ² |
| Wire Stripping Length | Auxiliary Circuit 10 mm Control Circuit 10 mm Main Circuit 10 mm |
| Degree of Protection | acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20 |
| Tightening Torque | Auxiliary Circuit 1.2 N·m Control Circuit 1.2 N·m Main Circuit 1.5 N·m |
| Terminal Type | Screw Terminals |
| Product Name | Contactor Starter |

Technical UL/CSA

| | |
|--|---|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V |
| Connecting Capacity Main Circuit UL/CSA | Rigid Solid 1/2x 16-10 AWG Rigid Stranded 1/2x 16-10 AWG |
| Connecting Capacity Auxiliary Circuit UL/CSA | Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG |
| Connecting Capacity Control Circuit UL/CSA | Rigid Solid 1/2x 18-14 AWG Rigid Stranded 1/2x 18-14 AWG |
| Tightening Torque UL/CSA | Auxiliary Circuit 11 in·lb Control Circuit 11 in·lb Main Circuit 13 in·lb |

Environmental

| | |
|-------------------------|---|
| Ambient Air Temperature | Close to Contactor Fitted with Thermal O/L Relay -25 ... 60 °C Close to Contactor without Thermal O/L Relay -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C |
| Pollution Degree | 3 |

Material Compliance

| | |
|---|--|
| Conflict Minerals Reporting Template (CMRT) | 9AKK108467A5658 |
| REACH Declaration | 2CMT2021-006202 |
| RoHS Information | 2CMT2021-006277 |
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
| Toxic Substances Control Act - TSCA | 2CMT2023-006525 |
| WEEE B2C / B2B | Business To Business |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

Certificates and Declarations

| | |
|----------------------|------------------------------------|
| A2L Certificate - UL | 9AKK108469A4875;9AKK108469A4879 |
| CB Certificate | CB_SE-113345 |
| UL Certificate | UL-US-2150887-5 UL-CA-2142658-5 |

Container Information

| | |
|------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Gross Weight | 2.162 kg |
| Package Level 1 EAN | 3471523020313 |

Classifications

| | |
|------------------------------------|--------------------------------------|
| ETIM 7 | EC000010 - Combination of contactors |
| ETIM 8 | EC000010 - Combination of contactors |
| ETIM 9 | EC000010 - Combination of contactors |
| eClass | V11.0 : 27371003 |
| UNSPSC | 39121529 |
| IDEA Granular Category Code (IGCC) | 4762 >> Nema Contactors |

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors → AF Contactors → AF12

