

AF50 - AF1650

Non-reversing, mechanically interlocked, reversing AC & DC operated, UL rated, 3 phase

Across the line
contactors

1



AF63-30-11-70



AF95-30-11-70



AF400-30-11-70



AF750-30-11-70

3 Pole

General purpose current	UL motor switching current	Maximum UL Listed motor horsepower ratings				Standard auxiliary contacts		Non-reversing		Mechanically interlocked		Reversing	
		208V	240V	480V	575/600V	NO	NC	Catalog number		Catalog number		Catalog number	
AC1													
80	54	15	20	40	50	1	1	AF50-30-11-70		AF50M-30-11-70		AF50R-30-11-70	
90	65	20	25	50	60	1	1	AF63-30-11-70		AF63M-30-11-70		AF63R-30-11-70	
105	80	25	30	60	75	1	1	AF75-30-11-70		AF75M-30-11-70		AF75R-30-11-70	
125	95	30	30	60	75	1	1	AF95-30-11-70		AF95M-30-11-70		AF95R-30-11-70	
140	110	30	40	75	100	1	1	AF110-30-11-70		AF110M-30-11-70		AF110R-30-11-70	
230	130	40	50	100	125	1	1	AF145-30-11-70		AF145M-30-11-70		AF145R-30-11-70	
250	156	50	60	125	150	1	1	AF185-30-11-70		AF185M-30-11-70		AF185R-30-11-70	
300	192	60	75	150	200	1	1	AF210-30-11-70		AF210M-30-11-70		AF210R-30-11-70	
350	248	75	100	200	250	1	1	AF260-30-11-70		AF260M-30-11-70		AF260R-30-11-70	
400	302	100	100	250	300	1	1	AF300-30-11-70		AF300M-30-11-70		AF300R-30-11-70	
550	414	125	150	350	400	1	1	AF400-30-11-70		AF400M-30-11-70		AF400R-30-11-70	
650	480	150	200	400	500	1	1	AF460-30-11-70		AF460M-30-11-70		AF460R-30-11-70	
750	602	200	250	500	600	1	1	AF580-30-11-70		AF580M-30-11-70		AF580R-30-11-70	
900	810	250	300	600	700	1	1	AF750-30-11-70		AF750M-30-11-70		AF750R-30-11-70	
1260	—	—	—	—	—	1	1	AF1250-30-11-70		—	—	—	—
1350	960	—	400	800	900	1	1	AF1350-30-11-70		—	—	—	—
1650	1080	—	450	900	1000	1	1	AF1650-30-11-70		—	—	—	—
2050	—	—	—	—	—	1	1	AF2050-30-11-70		—	—	—	—

Coil voltage selection – wide range AC/DC coils

All catalog numbers include a 100-250V AC/DC coil. To select other coil voltages, substitute the code from the Coil Voltage Selection Chart for the two digits after the last dash in the catalog number.

Ex.: A 24V coil is required for a AF110 contactor: AF110-30-11-72

Coil voltage selection – AF50 to AF1650

AC/DC VOLTS, 40 - 60 Hz				
24 - 60 DC	20 - 60 DC	48 - 130 AC/DC	100 - 250 AC/DC	250 - 500 AC//DC
68 1	72 2	69	70 3	71 4

1 AF400 – AF1250, DC only.

2 AF50 – AF300, DC only.

3 Only option for AF1350 - AF2050.

4 AF400 - AF750 only.