

Standard devices, ring-tongue, 3-pole

A/L9...A/F75

AC or DC controlled



A26..RT



A50...A75..RT

Electrical ratings

AC general purpose ratings (A)	Maximum motor switching current (A)	AC motor ratings, breaking all lines, three phase, 50/60 Hz (hp)				Standard auxiliary contacts		Catalog number, AC controlled	Catalog number, DC controlled
		200... 208V	220... 240V	440... 480V	550... 600V	NO	NC		
600V									
21	9	2	2	5	7.5	1	-	A93010RT-Δ	AL93010RT-Δ
						-	1	A93001RT-Δ	AL93001RT-Δ
25	11	3	3	7.5	10	1	-	A123010RT-Δ	AL123010RT-Δ
						-	1	A123001RT-Δ	AL123001RT-Δ
30	17	5	5	10	15	1	-	A163010RT-Δ	AL163010RT-Δ
						-	1	A163001RT-Δ	AL163001RT-Δ
40	28	7.5	10	20	25	1	-	A263010RT-Δ	AL263010RT-Δ
						-	1	A263001RT-Δ	AL263001RT-Δ
50	34	10	10	25	30	1	-	A303010RT-Δ	AL303010RT-Δ
						-	1	A303001RT-Δ	AL303001RT-Δ
60	42	10	15	30	40	1	-	A403010RT-Δ	AL403010RT-Δ
						-	1	A403001RT-Δ	AL403001RT-Δ
80	54	15	20	40	50	1	1	A503011RT-Δ	AF503011RT-Δ
90	68	20	25	50	60	1	1	A633011RT-Δ	AF633011RT-Δ
105	80	25	30	60	75	1	1	A753011RT-Δ	AF753011RT-Δ

Note: devices with ring-tongue termination UL recognized

Coil voltage selection chart (Δ)

Rated control circuit voltage U _c	A9... A75	AL9... AL40	AF50... AF75
12V DC	-	80	80
24V AC	81	-	-
24V DC	-	81	81
20...60V DC	-	-	72
110V/50, 110...120V/60	84	-	-
48...130V AC/DC	-	-	69
100...250V AC/DC	-	-	70
125V DC	-	87	87
220V DC	-	88	88
230...240V/60	80	-	-
240V DC	-	89	89
480V/60	51	-	-
600V/60	55	-	-

Example:

24V DC input voltage: AL303010RT-81

120V AC input voltage: A753011RT-84