

## PRODUCT-DETAILS

# AF80-30-11-41

## AF80-30-11-41 24-60V50/60HZ Contactor



### General Information

|                       |                                       |
|-----------------------|---------------------------------------|
| Extended Product Type | AF80-30-11-41                         |
| Product ID            | 1SBL397001R4111                       |
| EAN                   | 3471523133006                         |
| Catalog Description   | AF80-30-11-41 24-60V50/60HZ Contactor |

#### Long Description

AF80 contactors are used for controlling power circuits up to 690 V AC and 220 V DC. They are mainly used for controlling 3-phase motors, non-inductive or slightly inductive loads. AF... contactors include an electronic coil interface accepting a wide control voltage  $U_c$  min. ...  $U_c$  max. Only four coils cover control voltages between 24...500 V 50/60 Hz. AF contactors can manage large control voltage variations. One coil can be used for different control voltages used worldwide without any coil change. AF contactors have built-in surge protection and do not require additional surge suppressors. The AF... series 2-stack 3-pole contactors are of the block type design. - Main poles and auxiliary contact blocks: 3 main poles with side-mounted 1 N.O. + 1 N.C. auxiliary contact block, front-mounted add-on auxiliary contact blocks (mechanically-linked auxiliary contacts compliant with Annex L of IEC 60947-5-1 including the "Mechanically Linked" symbol on the contactor side. N.C. mirror contacts compliant with Annex F of IEC 60947-4-1) - Control circuit: AC operated - Accessories: a wide range of accessories is available. Note: 2-stack contactors available in some countries: please consult your ABB representative. AF..-30-..-11 not suitable for a direct control by PLC-output.

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85364900 |

## Popular Downloads

Instructions and  
Manuals

1SBC101036M6801

## Dimensions

|                               |          |
|-------------------------------|----------|
| Product Net Width             | 82 mm    |
| Product Net Depth /<br>Length | 116 mm   |
| Product Net Height            | 125.5 mm |
| Product Net Weight            | 1.26 kg  |

## Technical

|                                                       |                                                                                                                                                                                                                                                                                                                                                                                         |
|-------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of Main<br>Contacts NO                         | 3                                                                                                                                                                                                                                                                                                                                                                                       |
| Number of Main<br>Contacts NC                         | 0                                                                                                                                                                                                                                                                                                                                                                                       |
| Number of Auxiliary<br>Contacts NO                    | 1                                                                                                                                                                                                                                                                                                                                                                                       |
| Number of Auxiliary<br>Contacts NC                    | 1                                                                                                                                                                                                                                                                                                                                                                                       |
| Rated Operational<br>Voltage                          | Auxiliary Circuit 690 V<br>Main Circuit 1000 V                                                                                                                                                                                                                                                                                                                                          |
| Rated Frequency (f)                                   | Auxiliary Circuit 50 / 60 Hz<br>Main Circuit 50 / 60 Hz                                                                                                                                                                                                                                                                                                                                 |
| Conventional Free-air<br>Thermal Current ( $I_{th}$ ) | acc. to IEC 60947-4-1, Open Contactors q = 40 °C 130 A<br>acc. to IEC 60947-5-1, q = 40 °C 16 A                                                                                                                                                                                                                                                                                         |
| Rated Operational<br>Current AC-1 ( $I_e$ )           | (690 V) 40 °C 125<br>(690 V) 60 °C 100 A<br>(690 V) 70 °C 85                                                                                                                                                                                                                                                                                                                            |
| Rated Operational<br>Current AC-3 ( $I_e$ )           | (415 V) 60 °C 80 A<br>(440 V) 60 °C 80 A<br>(500 V) 60 °C 65 A<br>(690 V) 60 °C 49 A<br>(1000 V) 60 °C 25 A<br>(380 / 400 V) 60 °C 80 A<br>(220 / 230 / 240 V) 60 °C 80 A                                                                                                                                                                                                               |
| Rated Operational Power<br>AC-3 ( $P_e$ )             | (400 V) 37 kW<br>(415 V) 45 kW<br>(440 V) 45 kW<br>(500 V) 45 kW<br>(690 V) 45 kW<br>(1000 V) 35 kW<br>(380 / 400 V) 37 kW<br>(220 / 230 / 240 V) 22 kW                                                                                                                                                                                                                                 |
| Rated Operational<br>Current AC-15 ( $I_e$ )          | (500 V) 2 A<br>(690 V) 2 A<br>(24 / 127 V) 6 A<br>(220 / 240 V) 4 A<br>(400 / 440 V) 3 A                                                                                                                                                                                                                                                                                                |
| Rated Short-time<br>Withstand Current ( $I_{cw}$ )    | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 780 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 140 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 300 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1200 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 450 A<br>for 0.1 s 140 A<br>for 1 s 100 A |
| Maximum Breaking<br>Capacity                          | cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 1150 A<br>cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 750 A                                                                                                                                                                                                                                                           |
| Maximum Electrical<br>Switching Frequency             | (AC-1) 600 cycles per hour<br>(AC-15) 1200 cycles per hour<br>(AC-2 / AC-4) 150 cycles per hour<br>(AC-3) 1200 cycles per hour<br>(DC-13) 900 cycles per hour                                                                                                                                                                                                                           |

|                                               |                                                                                                                                                                                                                                                                           |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated Operational Current DC-13 ( $I_e$ )     | (24 V) 6 A / 144 W<br>(48 V) 2.8 A / 134 W<br>(72 V) 1 A / 72 W<br>(110 V) 0.55 A / 60 W<br>(125 V) 0.55 A / 69 W<br>(220 V) 0.27 A / 60 W<br>(250 V) 0.27 A / 68 W<br>(400 V) 0.15 A / 60 W<br>(500 V) 0.13 A / 65 W<br>(600 V) 0.1 A / 60 W                             |
| Rated Insulation Voltage ( $U_i$ )            | acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V<br>acc. to UL/CSA 600 V                                                                                                                                                                                                 |
| Rated Impulse Withstand Voltage ( $U_{imp}$ ) | 8 kV                                                                                                                                                                                                                                                                      |
| Maximum Mechanical Switching Frequency        | 3600 cycles per hour                                                                                                                                                                                                                                                      |
| Rated Control Circuit Voltage ( $U_c$ )       | 50 Hz 24 ... 60 V<br>50 Hz / 60 Hz 24 ... 60 V<br>60 Hz 24 ... 60 V<br>DC Operation -                                                                                                                                                                                     |
| Operate Time                                  | Between Coil De-energization and NC Contact Closing 19 ... 105 ms<br>Between Coil De-energization and NO Contact Opening 17 ... 100 ms<br>Between Coil Energization and NC Contact Opening 38 ... 95 ms<br>Between Coil Energization and NO Contact Closing 42 ... 100 ms |
| Connecting Capacity Main Circuit              | Flexible with Ferrule 1/2x 6 ... 50 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1/2x 6 ... 50 mm <sup>2</sup><br>Rigid 1x 6 ... 70 mm <sup>2</sup><br>Rigid 2x 6 ... 50 mm <sup>2</sup>                                                                            |
| Connecting Capacity Auxiliary Circuit         | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid 1/2x 1 ... 2.5 mm <sup>2</sup>                                     |
| Connecting Capacity Control Circuit           | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Rigid 1/2x 1 ... 2.5 mm <sup>2</sup>                                     |
| Wire Stripping Length                         | Main Circuit 17 mm                                                                                                                                                                                                                                                        |
| Degree of Protection                          | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP40<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10                                                                         |
| Terminal Type                                 | Screw Terminals                                                                                                                                                                                                                                                           |

## Technical UL/CSA

|                           |                                                                                                                                                                                                                                   |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General Use Rating UL/CSA | (600 V AC) 105 A                                                                                                                                                                                                                  |
| Horsepower Rating UL/CSA  | (120 V AC) Single Phase 7-1/2 hp<br>(200 ... 208 V AC) Three Phase 25 hp<br>(220 ... 240 V AC) Three Phase 30 hp<br>(240 V AC) Single Phase 15 hp<br>(440 ... 480 V AC) Three Phase 60 hp<br>(550 ... 600 V AC) Three Phase 75 hp |
| Tightening Torque UL/CSA  | Auxiliary Circuit 11 lA<br>Control Circuit 11 lA<br>Main Circuit 53 lA                                                                                                                                                            |

## Environmental

|                                        |                                                                                                                                                                                 |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature                | Close to Contactor Fitted with Thermal O/L Relay -25 ... +60 °C<br>Close to Contactor without Thermal O/L Relay -40 ... +70 °C<br>Close to Contactor for Storage -60 ... +80 °C |
| Climatic Withstand                     | Category B according to IEC 60947-1 Annex Q                                                                                                                                     |
| Maximum Operating Altitude Permissible | 3000 m                                                                                                                                                                          |
| Resistance to Vibrations               | 5 ... 300 Hz 3 g closed position / 3 g open position                                                                                                                            |

acc. to IEC 60068-2-6

Resistance to Shock acc.  
to IEC 60068-2-27Closed, Shock Direction: A 25 K40  
Closed, Shock Direction: B1 25 K40  
Closed, Shock Direction: B2 15 K40  
Closed, Shock Direction: C1 25 K40  
Closed, Shock Direction: C2 25 K40  
Open, Shock Direction: B1 5 K40

RoHS Status

Following EU Directive 2011/65/EU

## Certificates and Declarations (Document Number)

|                                   |                               |
|-----------------------------------|-------------------------------|
| ABS Certificate                   | ABS_15-GE1349500-PDA_90682247 |
| BV Certificate                    | BV_2634H36994A                |
| CB Certificate                    | CB_SE-96557                   |
| CCC Certificate                   | CCC_2013010304646569          |
| Declaration of<br>Conformity - CE | 1SBD250000U1000               |
| DNV Certificate                   | DNV-GL_TAE00001AF-3           |
| DNV GL Certificate                | DNV-GL_TAE00001AF-3           |
| EAC Certificate                   | EAC_RU_FRME77B03447           |
| Environmental<br>Information      | 1SBD250168E1000               |
| GL Certificate                    | DNV-GL_TAE00001AF-3           |
| Instructions and<br>Manuals       | 1SBC101036M6801               |
| KC Certificate                    | KC_HW02016-15011C             |
| LR Certificate                    | LRS_1300087E1                 |
| RINA Certificate                  | RINA_ELE084013XG              |
| RMRS Certificate                  | RMRS_1802705280               |
| RoHS Information                  | 1SBD250000U1000               |
| UL Certificate                    | UL_20130926-E312527_14_1      |
| UL Listing Card                   | UL_E312527                    |

## Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 150 mm        |
| Package Level 1 Depth /<br>Length | 150 mm        |
| Package Level 1 Height            | 103 mm        |
| Package Level 1 Gross<br>Weight   | 1.26 kg       |
| Package Level 1 EAN               | 3471523133006 |
| Package Level 2 Units             | box 8 piece   |
| Package Level 2 Width             | 250 mm        |
| Package Level 2 Depth /<br>Length | 300 mm        |
| Package Level 2 Height            | 300 mm        |
| Package Level 2 Gross<br>Weight   | 10.08 kg      |
| Package Level 3 Units             | 192 piece     |

## Classifications

|                               |                                           |
|-------------------------------|-------------------------------------------|
| Object Classification<br>Code | Q                                         |
| ETIM 4                        | EC000066 - Magnet contactor, AC-switching |
| ETIM 5                        | EC000066 - Magnet contactor, AC-switching |
| ETIM 6                        | EC000066 - Power contactor, AC switching  |

|                    |                                          |
|--------------------|------------------------------------------|
| ETIM 7             | EC000066 - Power contactor, AC switching |
| UNSPSC             | 39121529                                 |
| E-Number (Finland) | 3707124                                  |

---

**Categories**

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

