

Voltage code table

The below tables indicate the available coil voltages and corresponding digits for order codes. When placing an order, please give either type or order code. Select a standard contactor from ordering detail pages. Change the **coil voltage code** in the type or in the order code according to the table below. Example: for contactor AS09-30-10 and coil 42 V 50/60 Hz, type is AS09-30-10-**21** and order code is 1SBL101001R**21**10.

3-pole contactors

4

Type

AS16 - 30 - 10 - 26

Auxiliary contacts

N.O. N.C.

N.O. N.C.

Main contacts

AS

ASL

Contactor type

AC operated

DC operated

Order code

1SBL121001R 26 10

AC coil code

50 Hz 60 Hz

20

24 V

24 V

21

42 V

42 V

22

48 V

48 V

23

110 V

110 V

24

115 V

115 V

16

-

120 V

25

220 V

220 V

26

230 V

230 V

27

240 V

240 V

17

-

277 V

13

380 V

-

28

400 V

400 V

29

415 V

415 V

DC coil code

80

12 V

81

24 V

83

48 V

84

60 V

86

110 V

87

125 V

88

220 V

89

240 V

3-pole reversing contactors

Type

VAS12 S EM - 26 M

Surge suppressor

VAS

VASL

Contactor type

AC operated

DC operated

Order code

1SBK113800M 26 00

AC coil code

50 Hz 60 Hz

20

24 V

24 V

21

42 V

42 V

22

48 V

48 V

23

110 V

110 V

24

115 V

115 V

16

-

120 V

25

220 V

220 V

26

230 V

230 V

27

240 V

240 V

17

-

277 V

13

380 V

-

28

400 V

400 V

29

415 V

415 V

DC coil code

80

12 V (1)

81

24 V

83

48 V

84

60 V

86

110 V

87

125 V

88

220 V

89

240 V

(1) Not for VASL...SEM

Contactor relays

Type

NS 40 E - 26

N.O. N.C.

Number contacts

NS

NSL

Contactor type

AC operated

DC operated

Order code

1SBH101001R 26 40

AC coil code

50 Hz 60 Hz

20

24 V

24 V

21

42 V

42 V

22

48 V

48 V

23

110 V

110 V

24

115 V

115 V

16

-

120 V

25

220 V

220 V

26

230 V

230 V

27

240 V

240 V

17

-

277 V

13

380 V

-

28

400 V

400 V

29

415 V

415 V

DC coil code

80

12 V

81

24 V

83

48 V

84

60 V

86

110 V

87

125 V

88

220 V

89

240 V