# **Product datasheet**

Specifications

Green Premium



# Variable speed drive, ATV312, 0.55kW, 0.75hp, 170..264V, 1 phase supply, 3.7A, CANopen, Modbus

ATV312H055M2

() Discontinued

(!) Discontinued on: 26 Jan 2021

(!) End-of-service on: 17 Apr 2024

#### Main

| IVIAIII                               |   |  |
|---------------------------------------|---|--|
| Range of product                      | Altivar 312   |  |
| Product or component type             | Variable speed drive  |  |
| Product destination                   | Asynchronous motors   |  |
| Product specific application          | Simple machine  |  |
| Assembly style                        | With heat sink  |  |
| Component name                        | ATV312  |  |
| Motor power kW                        | 0.55 kW   |  |
| Motor power hp                        | 0.75 hp   |  |
| [Us] rated supply voltage             | 200240 V - 1510 %   |  |
| Supply frequency                      | 5060 Hz - 55 %  |  |
| Network number of phases              | Single phase  |  |
| Line current                          | 6.8 A at 200 V, Isc = 1 kA<br>5.8 A at 240 V  |  |
| EMC filter                            | Integrated  |  |
| Apparent power                        | 1.4 kVA   |  |
| Maximum transient current             | 5.6 A for 60 s  |  |
| Power dissipation in W                | 46 W at nominal load  |  |
| Speed range                           | 150   |  |
| Asynchronous motor control<br>profile | Sensorless flux vector control with PWM type motor control signal<br>Factory set : constant torque  |  |
| Electrical connection                 | Al1, Al2, Al3, AOV, AOC, R1A, R1B, R1C, R2A, R2B, LI1Ll6 terminal 2.5 mm²<br>AWG 14<br>L1, L2, L3, U, V, W, PA, PB, PA/+, PC/- terminal 2.5 mm² AWG 14  |  |
| Supply                                | Internal supply for logic inputs: 1930 V 100 mA, protection type: overload and short-circuit protection<br>Internal supply for reference potentiometer (2.2 to 10 kOhm): 1010.8 V 10 mA, protection type: overload and short-circuit protection |  |
| Communication port protocol           | CANopen<br>Modbus   |  |
| IP degree of protection               | IP20 on upper part without cover plate<br>IP21 on connection terminals<br>IP31 on upper part<br>IP41 on upper part  |  |

Communication card for CANopen daisy chain Communication card for DeviceNet Communication card for Fipio Communication card for Modbus TCP Communication card for Profibus DP

### Complementary

| Supply voltage limits       | 170264 V   |
|-----------------------------|--|
| Prospective line Isc        | 1 kA   |
| Continuous output current   | 3.7 A at 4 kHz   |
| Output frequency            | 0500 Hz  |
| Nominal switching frequency | 4 kHz  |
| Switching frequency         | 216 kHz adjustable   |
| Transient overtorque        | 170200 % of nominal motor torque   |
| Braking torque              | 150 % during 60 s with braking resistor<br>100 % with braking resistor continuously<br>150 % without braking resistor  |
| Regulation loop             | Frequency PI regulator   |
| Motor slip compensation     | Adjustable<br>Automatic whatever the load<br>Suppressable  |
| Output voltage              | <= power supply voltage  |
| Tightening torque           | AI1, AI2, AI3, AOV, AOC, R1A, R1B, R1C, R2A, R2B, LI1LI6: 0.6 N.m<br>L1, L2, L3, U, V, W, PA, PB, PA/+, PC/-: 0.8 N.m  |
| Insulation                  | Electrical between power and control   |
| Analogue input number       | 3  |
| Analogue input type         | Al1 configurable voltage 010 V, input voltage 30 V max, impedance: 30000 Ohm<br>Al2 configurable voltage +/- 10 V, input voltage 30 V max, impedance: 30000 Ohm<br>Al3 configurable current 020 mA, impedance: 250 Ohm   |
| Sampling duration           | AI1, AI2, AI3: 8 ms analog<br>LI1LI6: 4 ms discrete  |
| Response time               | AOV, AOC 8 ms for analog<br>R1A, R1B, R1C, R2A, R2B 8 ms for discrete  |
| Linearity error             | +/- 0.2 % for output   |
| Analogue output number      | 1  |
| Analogue output type        | AOC configurable current: 020 mA, impedance: 800 Ohm, resolution: 8 bits AOV configurable voltage: 010 V, impedance: 470 Ohm, resolution: 8 bits   |
| Discrete input logic        | Logic input not wired (LI1LI4), < 13 V (state 1)<br>Negative logic (source) (LI1LI6), > 19 V (state 0)<br>Positive logic (source) (LI1LI6), < 5 V (state 0), > 11 V (state 1)  |
| Discrete output number      | 2  |
| Discrete output type        | Configurable relay logic: (R1A, R1B, R1C) 1 NO + 1 NC - 100000 cycles<br>Configurable relay logic: (R2A, R2B) NC - 100000 cycles   |
| Minimum switching current   | R1-R2 10 mA at 5 V DC  |
| Maximum switching current   | R1-R2: 2 A at 250 V AC inductive load, cos phi = 0.4 and L/R = 7 ms<br>R1-R2: 2 A at 30 V DC inductive load, cos phi = 0.4 and L/R = 7 ms<br>R1-R2: 5 A at 250 V AC resistive load, cos phi = 1 and L/R = 0 ms<br>R1-R2: 5 A at 30 V DC resistive load, cos phi = 1 and L/R = 0 ms |
| Discrete input number       | 6  |
| Discrete input type         | (LI1LI6) programmable at 24 V, 0100 mA for PLC, impedance: 3500 Ohm  |

| Acceleration and deceleration ramps | S, U or customized<br>Linear adjustable separately from 0.1 to 999.9 s  |
|-------------------------------------|---|
| Braking to standstill               | By DC injection   |
| Protection type                     | Input phase breaks: drive<br>Line supply overvoltage and undervoltage safety circuits: drive<br>Line supply phase loss safety function, for three phases supply: drive<br>Motor phase breaks: drive<br>Overcurrent between output phases and earth (on power up only): drive<br>Overheating protection: drive<br>Short-circuit between motor phases: drive<br>Thermal protection: motor |
| Insulation resistance               | >= 500 mOhm 500 V DC for 1 minute   |
| Local signalling                    | 1 LED (red) for drive voltage<br>Four 7-segment display units for CANopen bus status  |
| Time constant                       | 5 ms for reference change   |
| Frequency resolution                | Analog input: 0.1100 Hz<br>Display unit: 0.1 Hz   |
| Connector type                      | 1 RJ45 for Modbus/CANopen   |
| Physical interface                  | RS485 multidrop serial link   |
| Transmission frame                  | RTU   |
| Transmission rate                   | 10, 20, 50, 125, 250, 500 kbps or 1 Mbps for CANopen<br>4800, 9600 or 19200 bps for Modbus  |
| Number of addresses                 | 1127 for CANopen<br>1247 for Modbus   |
| Number of drive                     | 127 for CANopen<br>31 for Modbus  |
| Marking                             | CE  |
| Operating position                  | Vertical +/- 10 degree  |
| Height                              | 145 mm  |
| Width                               | 72 mm   |
| Depth                               | 142 mm  |
| Product weight                      | 1.5 kg  |

#### Environment

| 2040 V DC between earth and power terminals   |
|---|
| 2880 V AC between control and power terminals   |
| ···· ······   |
| 1.2/50 $\mu s$ - 8/20 $\mu s$ surge immunity test level 3 conforming to IEC 61000-4-5 |
| Electrical fast transient/burst immunity test level 4 conforming to IEC 61000-4-4     |
| Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2             |
| Radiated radio-frequency electromagnetic field immunity test level 3 conforming to    |
| IEC 61000-4-3   |
| IEC 61800-5-1   |
| IEC 61800-3   |
| CSA   |
| UL  |
| GOST  |
| DNV   |
| C-Tick  |
| NOM   |
| 2   |
| TC  |
| 1 gn (f= 13150 Hz) conforming to EN/IEC 60068-2-6                                     |
| 1.5 mm (f= 313 Hz) conforming to EN/IEC 60068-2-6                                     |
|   |

| Shock resistance                      | 15 gn for 11 ms conforming to EN/IEC 60068-2-27   |
|---------------------------------------|---|
| Relative humidity                     | 595 % without condensation conforming to IEC 60068-2-3<br>595 % without dripping water conforming to IEC 60068-2-3                                    |
| Ambient air temperature for storage   | -2570 °C  |
| Ambient air temperature for operation | -1050 °C without derating (with protective cover on top of the drive)<br>-1060 °C with derating factor (without protective cover on top of the drive) |
| Operating altitude                    | <= 1000 m without derating<br>10002000 m with current derating 1 % per 100 m  |

### **Packing Units**

| Unit Type of Package 1       | PCE       |
|------------------------------|-----------|
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 13.5 cm   |
| Package 1 Width              | 18.0 cm   |
| Package 1 Length             | 17.5 cm   |
| Package 1 Weight             | 1.484 kg  |
| Unit Type of Package 2       | S06       |
| Number of Units in Package 2 | 48        |
| Package 2 Height             | 73.5 cm   |
| Package 2 Width              | 60 cm     |
| Package 2 Length             | 80 cm     |
| Package 2 Weight             | 84.232 kg |

### **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

#### Well-being performance

Mercury Free

Rohs Exemption Information

#### **Certifications & Standards**

| Eu Rohs Directive     | Pro-active compliance (Product out of EU RoHS legal scope)   |
|-----------------------|--|
|                       | EU RoHS Declaration  |
| China Rohs Regulation | China RoHS declaration   |
| Weee                  | The product must be disposed on European Union markets following specific waste<br>collection and never end up in rubbish bins |
| Circularity Profile   | End of Life Information  |