# **Product data sheet**

Specifications





servo motor BCH, Lexium 28, 130mm, 2000W, 13.5kg.cm², without oil seal, with key, straight connection

BCH2MM2021CA6C



! Discontinued on: Oct 9, 2023

Product availability: Non-Stock - Not normally stocked in distribution facility

#### Main

Range Compatibility	Lexium 28
Device short name	BCH2
Product or Component Type	Servo motor

## Complementary

Maximum mechanical speed	3000 rpm
[Us] rated supply voltage	220 V
Phase	Three phase
Continuous stall current	9.95 A
Continuous stall torque	84.52 lbf.in (9.55 N.m) LXM28 12 A, 220 V, three phase
Continuous power	2000 W
Peak stall torque	253.57 lbf.in (28.65 N.m) LXM28 12 A, 220 V, three phase
Nominal output power	2000 W LXM28 12 A, 220 V, three phase
Nominal torque	84.52 lbf.in (9.55 N.m) LXM28 12 A, 220 V, three phase
Nominal speed	2000 rpm LXM28 12 A, 220 V, three phase
Maximum current Irms	32.85 A LXM28 2 kW, 220 V
Maximum permanent current	11.25 A
Product compatibility	LXM28 servo drive 2 kW, 220 V, three phase
Shaft end	Keyed
Shaft diameter	0.9 in (22 mm)
Shaft length	2.2 in (55 mm)
Key width	0.3 in (8 mm)
Feedback type	20 bits single turn absolute encoder
Holding brake	Without
Mounting Support	Asian standard flange
Motor flange size	5.1 in (130 mm)
Electrical connection	Connector MIL
Torque constant	0.96 N.m/A 68 °F (20 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Back emf constant	58 V/krpm 68 °F (20 °C)
Rotor inertia	13.5 kg.cm <sup>2</sup>
Stator resistance	0.34 Ohm 68 °F (20 °C)
Stator inductance	4.5 mH 68 °F (20 °C)
Stator electrical time constant	13.24 ms 68 °F (20 °C)
Maximum radial force Fr	670 N 2000 rpm
Maximum axial force Fa	200 N
Brake pull-in power	19.7 W
Type of cooling	Natural convection
Length	7.4 in (187 mm)
Number of motor stacks	4
Centring collar diameter	4.3 in (110 mm)
Centring collar depth	0.3 in (8 mm)
Number of mounting holes	4
Mounting holes diameter	0.4 in (9.2 mm)
Circle diameter of the mounting holes	5.7 in (145 mm)
Distance shaft shoulder-flange	0.3 in (8 mm)
Net Weight	21.4 lb(US) (9.7 kg)

# **Environment**

IP Degree of Protection	IP54 IM B5, IM V1 IP50 IM V3
Ambient Air Temperature for Operation	-4104 °F (-2040 °C)

# Ordering and shipping details

Category	US1PC5318281
Discount Schedule	PC53
GTIN	3606480734380
Returnability	No
Country of origin	CN

# **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.1 in (18.1 cm)
Package 1 Width	9.06 in (23.0 cm)
Package 1 Length	14.2 in (36.0 cm)
Package 1 Weight	19.67 lb(US) (8.92 kg)



**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

## Well-being performance

	Reach Free Of Svhc
<b>②</b>	Mercury Free
<b>⊘</b>	Rohs Exemption Information Yes
<b>⊘</b>	Pvc Free


# **Certifications & Standards**

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China Rohs Regulation	China RoHS declaration	
Environmental Disclosure	Product Environmental Profile	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.	
Circularity Profile	End of Life Information	
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	

#### **Dimensions Drawings**

#### **Dimensions**

#### **Dimensions of Motor**



	mm	in.
L (without holding brake)	187	7.36
L (with holding brake)	216	8.5
Z	134.5	5.30


# Product data sheet BCHS

# BCH2MM2021CA6C

#### Performance Curves

#### Torque/Speed Curves with 230 V Three Phase Supply Voltage

## Servo Motor with LXM28AU20●●● Servo Drive



- 1: Peak torque
- 2: Continuous torque